

### US00D395980S

# United States Patent [19]

## Boisselier

[56]

[11] Patent Number: Des. 395,980 [45] Date of Patent: \*\*Jul. 14, 1998

[54]	FRYER	
[75]	Inventor:	Pierre Boisselier, Selongey, France
[73]	Assignee:	SEB, Selongey, France
[**]	Term:	14 Years
[21]	Appl. No.:	72,801
[22]	Filed:	Jun. 30, 1997
[51]	LOC (6)	Cl 07-02
	Field of Search	
		D7/360; 99/331, 336, 385, 403, 410, 411
		413; 219/429, 432, 438, 440

# References Cited

#### U.S. PATENT DOCUMENTS

D. 323,762	2/1992	Barrault
,		Chang
		Powell
D. 369,270	4/1996	Payen D7/323 X
D. 369,505		Philippe D7/323 X
·		

Primary Examiner—Caron D. Veynar

Attorney, Agent, or Firm-Loeb & Loeb LLP

[57]

CLAIM

The ornamental design for a fryer, as shown and described.

#### **DESCRIPTION**

FIG. 1 is a perspective view of a fryer showing my new design;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof;

FIG. 4 is a left side elevational view thereof;


FIG. 5 is a top plan view thereof;


FIG. 6 is a bottom plan view thereof; and,

FIG. 7 is a rear elevational view thereof.


The design is characterized by the shape of the fryer, the body of which has a generally cylindrical side wall. In the middle of the lid there is a handle with recesses on both sides of the handle. A series of generally parallel, narrow, curved apertures are visible on the lid. At the front of the body of the fryer, near the bottom, there is visible a protruding portion having an upper edge in the form of an arch. An oval temperature control button is located at the bottom of the protruding portion. The body has two handles, each located on a respective side of the fryer.

## 1 Claim, 4 Drawing Sheets





F/G. 1



Jul. 14, 1998

FIG. 2






FIG. 3



Jul. 14, 1998

FIG. 4



U.S. Patent Jul. 14, 1998 Sheet 4 of 4 Des. 395,980

