



US00D397029S

United States Patent [19]

Preuss

[11] Patent Number: **Des. 397,029**

[45] Date of Patent: ****Aug. 18, 1998**

[54] **ROPE SECURING DEVICE FOR HOLDING A ROPE UNDER TENSION**

[76] Inventor: **James A. Preuss**, 4032 Alex La., Carmichael, Calif. 95608

[**] Term: **14 Years**

[21] Appl. No.: **68,484**

[22] Filed: **Mar. 21, 1997**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 677,841, Jul. 10, 1996, abandoned.

[51] LOC (6) Cl. **08-08**

[52] U.S. Cl. **D8/383**

[58] Field of Search **D8/383; 24/115 M, 24/136 R, 134 R, 134 KB**

[56] References Cited

U.S. PATENT DOCUMENTS

- 881,041 3/1908 Almstead .
- 1,012,587 12/1911 Ballul 24/134 R
- 1,067,412 7/1913 Eckhardt et al. .
- 1,250,876 12/1917 Hicks .
- 1,522,400 1/1925 Wagenbrenner 24/134 R

- 2,845,674 8/1958 Pearson .
- 2,942,315 6/1960 Johnson 24/134 R
- 3,256,579 6/1966 Hoover .
- 3,437,981 4/1969 Keller .
- 4,878,270 11/1989 Westerkamp .
- 5,133,111 7/1992 Brown .
- 5,423,108 6/1995 Brennan 24/134 R

FOREIGN PATENT DOCUMENTS

- 129865 1/1929 Switzerland 24/134 R

Primary Examiner—B. J. Bullock


[57] CLAIM

The ornamental design for a rope securing device for holding a rope under tension, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a rope securing device for holding a rope under tension showing my new design; a back view thereof appears as a mirror image of the front view; FIG. 2 is a right side view thereof; FIG. 3 is a left side view thereof; FIG. 4 is a top view thereof; FIG. 5 is a bottom view thereof; and, FIG. 6 is a front right side perspective view thereof.

1 Claim, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6