

US00D397076S

United States Patent [19]

Seibert et al.

[11] Patent Number: Des. 397,076

[45] Date of Patent: **Aug. 18, 1998

[54] TANK CAP FOR MOTOR VEHICLES

[76] Inventors: Ralph Seibert, Adalbert-Stifter-Strasse

1, D-35428 Langgöns; Norbert Wolff,

Junkernstrasse 2, D-35460 Staufenberg,

both of Germany

[**] Term: 14 Years

[21] Appl. No.: 64,462

[22] Filed: Jan. 2, 1997

Related U.S. Application Data

[63]	Continuation-in-part	of	Ser.	No.	43,907,	Aug.	14,	1995,
	abandoned.							

[51]	LOC (6) Cl.		12-16
[60]	TIC CI	T\	14/167

210, 288, DIG. 32, DIG. 33

[56] References Cited

U.S. PATENT DOCUMENTS

Ι	D. 25 0,468	12/1978	O'Banion
	2,796,162	6/1957	Nehls 220/210
	3,478,922	11/1969	Mole 220/86.2
	3,945,454	3/1976	Kinoshita et al 220/210 X
	4,091,959	5/1978	O'Banion 220/86.2 X
	4,099,645	7/1978	Muth et al 220/86.2 X
	4,228,915	10/1980	Hooper et al 220/288
	5,000,339	3/1991	Wheat et al 220/DIG. 33
	5,096,154	3/1992	Ellis 220/288 X

Primary Examiner—Alan P. Douglas
Assistant Examiner—Lavone D. Tabor
Attorney, Agent, or Firm—Edmund M. Jaskiewicz

[57] CLAIM

The ornamental design for a tank cap for motor vehicles, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the tank cap for motor vehicles viewed from the side, and from above with the key cover open showing our new design;

FIG. 2 is a perspective view similar to that of FIG. 1 but showing the tank cap with a left-hand thread and the key cover closed;

FIG. 3 is a top plan view thereof;

FIG. 4 is a side elevational view thereof;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a perspective view of the tank cap for motor vehicles viewed from the side, and from above with the key cover open showing a modification of our new design;


FIG. 7 is a perspective view thereof viewed from the opposite side and from above but with the key cover closed; FIG. 8 is a top plan view thereof; and,


FIG. 9 is a side elevational view thereof.


Except for the positions of the conventional threading on the base and the ovate protrusion on the key cover, the front and rear of the cap of FIG. 1-5 are the same in appearance as the side that is shown in FIG. 4.

Except for the positions of the conventional threading on the base and the ovate protrusion on the key cover, the front and rear of the cap of FIGS. 6-9 are the same in appearance as the side that is shown in FIG. 9. The bottom of the modification cap is the same in appearance as in FIG. 5.


1 Claim, 5 Drawing Sheets









F/G. 1




F/G. 2




F/G. 3




F/G. 4



F/G. 5




F/G. 6




F/G. 7

U.S. Patent



F/G. 8



F/G. 9