



US00D397162S

United States Patent [19]

Yokoi et al.

[11] Patent Number: Des. 397,162

[45] Date of Patent: **Aug. 18, 1998

[54] CONTROLLER FOR GAME MACHINE

[75] Inventors: Gunpei Yokoi; Hideo Nagata; Kenichi Sugino; Yuji Hori; Norikatsu Furuta, all of Kyoto, Japan

[73] Assignee: Nintendo of America, Inc., Redmond, Wash.

[**] Term: 14 Years

[21] Appl. No.: 39,778

[22] Filed: May 1, 1995

[30] Foreign Application Priority Data

Nov. 11, 1994 [JP] Japan 6-34522
Nov. 11, 1994 [JP] Japan 6-34525
Apr. 4, 1995 [JP] Japan 7-9417

[51] LOC (6) Cl. 21-01

[52] U.S. Cl. D21/48

[58] Field of Search D21/1, 13, 48;
273/433-438, 148 B, DIG. 28; D14/217,
124, 125

[56] References Cited

U.S. PATENT DOCUMENTS

D. 316,879 5/1991 Shulman et al. D21/48
D. 317,946 7/1991 Tse D21/48
D. 357,712 4/1995 Wu D21/48
D. 363,092 10/1995 Hung D21/48
5,203,563 4/1993 Loper, III 273/148 B
5,290,343 3/1994 Hineman 273/438 X

FOREIGN PATENT DOCUMENTS

6054962 3/1994 Japan 273/438

OTHER PUBLICATIONS

Hong Kong Enterprise, 1985, p. 9.
Play Things, 1988, p. 50.

Primary Examiner—Prabhakar Deshmukh
Attorney, Agent, or Firm—Nixon & Vanderhye P.C.

[57] CLAIM

The ornamental design for a “controller for game machine”, as shown and described.

DESCRIPTION

FIG. 1 is a front right perspective view of a controller for game machine in accordance with the first embodiment of our new design;
FIG. 2 is a rear left perspective view of the first embodiment of our new design;
FIG. 3 is a top plan view thereof;
FIG. 4 is a front elevation view thereof;
FIG. 5 is a rear elevation view thereof;
FIG. 6 is a bottom plan view thereof;
FIG. 7 is a right side view thereof, the left side view being identical thereto;
FIG. 8 is a front right perspective view of the embodiment shown in FIGS. 1-7, but with detachable battery pack portion removed therefrom;
FIG. 9 is a rear left perspective view of the embodiment illustrated in FIG. 8;
FIG. 10 is a top plan view thereof;
FIG. 11 is a front elevation view thereof;
FIG. 12 is a bottom plan view thereof;
FIG. 13 is a rear elevation view thereof;
FIG. 14 is a right side view thereof, the left side view being identical thereto;
FIG. 15 is a front right perspective view of a controller for game machine in accordance with a second embodiment of our new design;
FIG. 16 is a rear left perspective view thereof;
FIG. 17 is a top plan view thereof;
FIG. 18 is a front elevation view thereof;
FIG. 19 is a rear elevation view thereof;
FIG. 20 is a bottom plan view thereof;
FIG. 21 is a right side view thereof, the left side view being identical thereto;
FIG. 22 is a front right perspective view of the embodiment illustrated in FIG. 15, but with a detachable battery pack portion removed therefrom;
FIG. 23 is a rear left perspective view thereof;
FIG. 24 is a top plan view thereof;
FIG. 25 is a front elevation view thereof;
FIG. 26 is a bottom plan view thereof;
FIG. 27 is a rear elevation view thereof; and,




FIG. 28 is a right side view thereof, the left side view being identical thereto.

1 Claim, 14 Drawing Sheets

FIG. 1





FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6

FIG. 7





FIG. 8






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

FIG. 15





FIG. 16






FIG. 17




FIG. 18

FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23





FIG. 24






FIG. 25




FIG. 26

FIG. 27




FIG. 28

