



US00D398058S

**United States Patent** [19]  
**Collier**

[11] **Patent Number: Des. 398,058**

[45] **Date of Patent: \*\*Sep. 8, 1998**

[54] **PROSTHETIC BRACE**

5,658,353 8/1997 Layton ..... 623/34

[76] Inventor: **Milo S. Collier**, 6009 NW. 289th St.,  
Ridgefield, Wash. 98642

*Primary Examiner*—Louis S. Zarfes  
*Assistant Examiner*—Gregory Andoll  
*Attorney, Agent, or Firm*—Kolisch, Hartwell, Dickinson,  
McCormack & Heuser

[\*\*] Term: **14 Years**

[21] Appl. No.: **72,991**

[57] **CLAIM**

[22] Filed: **Jun. 27, 1997**

The ornamental design for a prosthetic brace, as shown and described.

[51] **LOC (6) Cl.** ..... **24-03**

[52] **U.S. Cl.** ..... **D24/155**

[58] **Field of Search** ..... D24/155; 623/26–28,  
623/32–36, 38

**DESCRIPTION**

[56] **References Cited**


**U.S. PATENT DOCUMENTS**

D. 364,925	12/1995	Pye	.....	D24/155
3,422,462	1/1969	Finnieston	.....	623/33
4,704,129	11/1987	Massey	.....	623/32
4,988,360	1/1991	Shamp	.....	623/33
5,108,456	4/1992	Coonan, III	.....	623/33
5,246,464	9/1993	Sabolich	.....	623/33

FIG. 1 is a right side view of a prosthetic brace constructed in accordance with a preferred embodiment of the invention; FIG. 2 is a front view thereof; FIG. 3 is a rear view thereof; FIG. 4 is a left side view thereof; FIG. 5 is a bottom view thereof; and, FIG. 6 is a top view thereof.

The prosthetic brace is hollow with a substantially uniform wall thickness throughout.

**1 Claim, 1 Drawing Sheet**






FIG. 2




FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 6