



US00D400831S

United States Patent [19]
Blankenship et al.

[11] **Patent Number: Des. 400,831**

[45] **Date of Patent: **Nov. 10, 1998**

[54] **TIRE TREAD**

[75] Inventors: **Leonard F. Blankenship**, Sterling;
James G. Guspodin, Akron; **Bradley J. Wurst**, Orrville, all of Ohio

[73] Assignee: **Bridgestone/Firestone, Inc.**, Akron, Ohio

[**] Term: **14 Years**

[21] Appl. No.: **72,612**

[22] Filed: **Jun. 20, 1997**

[51] **LOC (6) Cl.** **12-15**

[52] **U.S. Cl.** **D12/147**

[58] **Field of Search** D12/134, 136,
D12/138, 140-151; 152/209 R, 209 A,
209 D

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 338,179	8/1993	Miller et al.	D12/147
D. 345,952	4/1994	Christenbury	D12/147
D. 364,594	11/1995	Krupa et al.	D12/147
D. 369,768	5/1996	Wakamatsu et al.	D12/147
D. 384,618	10/1997	Guspodin et al.	D12/147
D. 384,923	10/1997	Allen et al.	D12/147
D. 386,454	11/1997	Guspodin	D12/147
5,501,258	3/1996	Sulkowski	152/209 R

OTHER PUBLICATIONS

Atlas Pinnacle TE Tire, 1996 Tread Design Guide, p. 9, Feb. 1996.

Gillette Golden Bear Touring SE Tire, 1996 Tread Design Guide, p. 31, Feb. 1996.

Hercules HP 7000 Tire, 1996 Tread Design Guide, p. 37, Feb. 1996.

Primary Examiner—Robert M. Spear
Attorney, Agent, or Firm—Carmen Santa Maria

[57] **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a side perspective view of a tire tread showing our new design, it being understood that the tread pattern is repeated throughout the circumference of the tire tread, the opposite side being the same as that shown;

FIG. 2 is a front elevational view thereof;


FIG. 3 is a side elevational view of the right side thereof, the opposite side being identical thereto; and,

FIG. 4 is an enlarged fragmentary front elevational view thereof.

The broken lines defining the tire inner bead and the peripheral boundary between the tire bead and the sidewall are for illustrative purposes only and form no part of the claimed design.

The dark stippled surface shading represents the recessed portion of the tread grooves, having a depth as best shown in FIG. 2.

1 Claim, 4 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4