

US00D401175S

United States Patent [19]

Bender et al.

[11] Patent Number: Des. 401,175

[45] Date of Patent: **Nov. 17, 1998

[54] OCCUPANCY SENSOR

[75] Inventors: R. Kurt Bender, Dripping Springs,

Tex.; Willfred Goldschmidt, Weston; Justin F. Aiello, Norwalk, both of

Conn.

[73] Assignee: Mytech Corporation, Austin, Tex.

[**] Term: 14 Years

[21] Appl. No.: **68,019**

[22] Filed: Mar. 17, 1997

D10116, 121; 340/540, 545, 571, 572, 573, 600, 613, 666, 693

[56] References Cited

U.S. PATENT DOCUMENTS

D. 320,7	58 1	0/1991	Lutz et al	D10/104
D. 339,0	78	9/1993	Behlke	D10/106
D. 377,4	60	1/1997	Nelson et al	D10/106
D. 386,1	03 1	1/1997	Kawabata	D10/106
D. 388,3	52 1	2/1997	Repp et al	D10/106
5,128,6	54	7/1992	Griffin et al	340/567
5,142,1	99	8/1992	Elwell	315/154
5,221,9	19	6/1993	Hermans	340/567
5,258,8	99 1	1/1993	Chen et al	362/395
5,281,9	61	1/1994	Elwell	340/825
5,282,1	18	1/1994	Lee	362/276
5,293,0	97	3/1994	Elwell	315/154

OTHER PUBLICATIONS

Novitas Brochure "Novitas™ Introduces The Two–Level Automatic Wall Switch For Maximum Convenience," Novitas, Inc., 1991.

Novitas Brochure "Model 01–110 Two–Way Room and Garage Sensor," ©Novitas, Inc., 1993.

Novitas Brochure "Model 01–100 One–Way Room Sensor," ©Novitas, Inc., 1993.

Novitas Brochure "Model 01–092 Corridor & Warehouse Sensor," ©Novitas, Inc. 1986, 1990.

Unenco® Brochure "Occupancy Sensor for Lighting and HVAC Controls," Universal Energy Control, Inc.

Unenco® Brochure "Occupancy Sensors for Lighting and HVAC Controls, Combo Dual Technology Sensor," Unenco®, 1994.

Unenco® Brochure "Occupancy Sensor for Lighting and HVAC Controls, Conserver™ Model C–500–800 and Model C–50–2000," Unenco®, 1994.

Unenco® Brochure "Occupancy Sensors for Lighting and HVAC Controls, Conserver™ PIR–500–P Series B and PIR–100 Series B Passive Infrared Ceiling–Mounted Sensors," Unecno©, 1994.

Unenco® Brochure"Occupancy Sensors for Lighting and HVAC Controls, Daylight Tracker™ Photoelectric Light Level Control," Unenco©, 1994.

SensorswitchTM Brochure "No Known Equal," Sensor Switch, Inc.

The Watt Stopper® Brochure "Decorator Automatic Wall Switch," The Watt Stopper, Inc.

The Watt Stopper® Brochure "Passive Infrared Wall Switch," The Watt Stopper, Inc.

The Watt Stopper® Brochure "Passive Infrared Sensor," The Watt Stopper, Inc.

The Watt Stopper® Brochure "CI Passive Infrared Sensor," The Watt Stopper, Inc.

The Watt Stopper® Brochure "Ultrasonic Sensors," The Watt Stopper, Inc.

The Watt Stopper® Brochure "Dual Technology Sensor," The Watt Stopper, Inc.

The Watt Stopper® Brochure "LightSaver Controller," The Watt Stopper, Inc.

Primary Examiner—Marcus A. Jackson Attorney, Agent, or Firm—Arnold, White & Durkee


[57] CLAIM

The design for an occupancy sensor, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the bottom, front and right sides of a first embodiment of the occupancy sensor showing the new and ornamental design;

FIG. 2 is a perspective view of the bottom, back and left sides of the occupancy sensor of FIG. 1;





- FIG. 3 is a perspective view of the bottom, front and right sides of a second embodiment of the occupancy sensor showing the new and ornamental design;
- FIG. 4 is a perspective view of the bottom, back and left sides of the occupancy sensor of FIG. 3;
- FIG. 5 is a perspective view of the bottom, front and right sides of a third embodiment of the occupancy sensor showing the new and ornamental design;
- FIG. 6 is a perspective view of the bottom, back and left sides of the occupancy sensor of FIG. 5;
- FIG. 7 is a perspective view of the bottom, front and right sides of a fourth embodiment of the occupancy sensor showing the new and ornamental design;


- FIG. 8 is a perspective view of the bottom, back and left sides of the occupancy sensor of FIG. 7;
- FIG. 9 is a perspective view of the bottom, front and right sides of a fifth embodiment of the occupancy sensor showing the new and ornamental design; and,
- FIG. 10 is a perspective view of the bottom, back and left sides of the occupancy sensor of FIG. 9.


The bottom of the claimed design is unornamented.


1 Claim, 5 Drawing Sheets











UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : D401,175

Page 1 of 2

DATED

: November 17, 1998

INVENTOR(S): R. Kurt Bender, et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Figures, delete Figures 5-10.

In the Description: page 2, delete:

"FIG. 5 is a perspective view of the bottom, front and right sides of a third embodiment of the OCCUPANCY SENSOR showing the new and ornamental design.

FIG. 6 is a perspective view of the bottom, back and left sides of the OCCUPANCY SENSOR of FIG. 5.

FIG. 7 is a perspective view of the bottom, front and right sides of a fourth embodiment of the OCCUPANCY SENSOR showing the new and ornamental design.

FIG. 8 is a perspective view of the bottom, back and left sides of the OCCUPANCY SENSOR of FIG. 7.

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : D401,175

Page 2 of 2

DATED

: November 17, 1998

INVENTOR(S): R. Kurt Bender, et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

FIG. 9 is a perspective view of the bottom, front and right sides of a fifth embodiment of the OCCUPANCY SENSOR showing the new and ornamental design.

FIG. 10 is a perspective view of the bottom, back and left sides of the OCCUPANCY SENSOR of FIG. 9."

Signed and Sealed this

Fifteenth Day of May, 2001

Attest:

NICHOLAS P. GODICI

Milalas P. Belai

Attesting Officer

Acting Director of the United States Patent and Trademark Office