



US00D401896S

United States Patent [19]

Chandler et al.

[11] Patent Number: **Des. 401,896**

[45] Date of Patent: ****Dec. 1, 1998**

[54] TIRE

[75] Inventors: **Graeme Alfred Chandler**, Morley;
Gregory Richard Haydon, Sorrento;
Stephen Harwood, Wembley; **Brian Frank Mangano**, Crawley, all of Australia

[73] Assignee: **Airboss Tyres Pty Ltd**, Australia

[**] Term: **14 Years**

[21] Appl. No.: **61,491**

[22] Filed: **Oct. 24, 1996**

[30] Foreign Application Priority Data

May 3, 1996	[AU]	Australia	1352/96
May 3, 1996	[AU]	Australia	1353/96

[51] LOC (6) Cl. **12-15**

[52] U.S. Cl. **D12/152; D12/149**

[58] Field of Search D12/134, 136,
D12/138-151; 152/209 D, 209 R

[56] References Cited

U.S. PATENT DOCUMENTS

D. 61,150	7/1922	Boucher	D12/146
D. 68,536	10/1925	Lenhoff	D12/139
D. 85,055	9/1931	Reichard	D12/146
D. 114,528	5/1939	Burgess	D12/139
D. 201,238	5/1965	Fishman	D12/146
D. 329,413	9/1992	Chandler	D12/151
957,168	5/1910	Kempshall	152/209 R
1,430,100	9/1922	Mitchell	152/209 R
3,196,920	7/1965	Fishman	D12/146 X
3,770,038	11/1973	Wolfe	D12/134 X

OTHER PUBLICATIONS

Lodi #5 Drag Slick, *Tires—TBA Merchandising*, Jun. 1958, p. 64.

U.S. Royal Road Roller tire, *U.S. Royal Tubeless and Tubed Off-Road Tires Sales and Engineering Manual*.

Galaxy Super Sidewall Skid Steer tire, *1994 Tread Design Guide*, p. 167, top row, center.

Goodyear SGG-2A tire, *1994 Tread Design Guide*, p. 171, bottom row, second from left.

Toyo G-25EDT tire, *1994 Tread Design Guide*, p. 175, top row, center.

Primary Examiner—Robert M. Spear
Attorney, Agent, or Firm—Handal & Morofsky

[57] CLAIM

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a side elevational view of a tire showing our new design with a portion thereof cut away for ease of disclosure, it being understood that the structure continues uniformly throughout the circumference of the tire;

FIG. 2 is a front elevational view thereof, it being understood that the tread pattern continues uniformly throughout the circumference of the tire;

FIG. 3 is a side elevational view thereof, the opposite side elevational view being identical thereto;

FIG. 4 is a cross-sectional view thereof, taken on line 4—4 of FIG. 3;


FIG. 5 is a side elevational view of a second embodiment of a tire showing our new design with a portion thereof cut away for ease of disclosure, it being understood that the structure continues uniformly throughout the circumference of the tire;

FIG. 6 is a front elevational view thereof, it being understood that the tread pattern continues uniformly throughout the circumference of the tire;

FIG. 7 is a side elevational view thereof, the opposite side elevational view being identical thereto; and,

FIG. 8 is a cross-sectional view thereof, taken on line 8—8 of FIG. 7.

1 Claim, 8 Drawing Sheets






Fig. 1.




Fig. 2




Fig. 3.




Fig. 4




Fig. 5.




FIG. 6.




Fig. 7.




Fig. 8