



US00D404019S

United States Patent [19]

[11] Patent Number: **Des. 404,019**

Lindsley et al.

[45] Date of Patent: ****Jan. 12, 1999**

[54] **RETICLE HOLDER**

[75] Inventors: **Robert K. Lindsley**, Colorado Springs;
Joseph A. Durben, Woodland Park;
Charles D. Travis, Colorado Springs,
all of Colo.

[73] Assignee: **Microtome Precision, Inc.**, Colorado Springs, Colo.

[**] Term: **14 Years**

[21] Appl. No.: **71,858**

[22] Filed: **May 15, 1997**

[51] **LOC (6) Cl.** **13-03**

[52] **U.S. Cl.** **D13/184**

[58] **Field of Search** D13/182, 199;
206/328; 211/41; 361/769, 797

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 274,809	7/1984	Revah et al.	D13/182
D. 288,804	3/1987	Hakanen	D13/184
D. 380,454	7/1997	Iwai et al.	D13/184
D. 391,232	2/1998	Hartel et al.	D13/184

OTHER PUBLICATIONS

Photographs 1, 2, 3 of similar device on sale in United States more than one year prior to filing date of best of application, to the best of applicant's information and belief.
Photographs 4, 5, 6 of similar device on sale in United States more than one year prior to filing date of application, to the best of applicant's information and belief.

Photographs 7, 8, 9 of similar device on sale in United States more than one year prior to filing date of application, to the best of applicant's information and belief.

Primary Examiner—Brian N. Vinson
Attorney, Agent, or Firm—Richard A. Bachand



[57] **CLAIM**

The ornamental design for a reticle holder, as shown.

DESCRIPTION

FIG. 1 is a top front isometric view of a reticle holder according to a preferred embodiment of the present invention;
FIG. 2 is a rear bottom isometric view of the reticle holder of FIG. 1;
FIG. 3 is a front elevation of the reticle holder of FIG. 1;
FIG. 4 is a bottom plan view of the reticle holder of FIG. 1;
FIG. 5 is a top plan view of the reticle holder of FIG. 1;
FIG. 6 is a rear elevation of the reticle holder of FIG. 1;
FIG. 7 is a left elevation of the reticle holder of FIG. 1;
FIG. 8 is a right elevation of the reticle holder of FIG. 1;
FIG. 9 is a top front isometric view of the reticle holder according to another preferred embodiment of the present invention;
FIG. 10 is a rear bottom isometric view of the reticle holder of FIG. 9;
FIG. 11 is a top plan view of the reticle holder of FIG. 9;
FIG. 12 is a front elevation of the reticle holder of FIG. 9;
FIG. 13 is a rear elevation of the reticle holder of FIG. 9;
FIG. 14 is a bottom plan view of the reticle holder of FIG. 9;
FIG. 15 is a left elevation of the reticle holder of FIG. 9; and,
FIG. 16 is a right elevation of the reticle holder of FIG. 9.

1 Claim, 10 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 6




Fig. 5




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 12




Fig. 11




Fig. 14




Fig. 13




Fig. 16




Fig. 15