



US00D404927S

United States Patent [19]

Blomdell et al.

[11] **Patent Number: Des. 404,927**

[45] **Date of Patent: **Feb. 2, 1999**

[54] **VEHICLE SEAT**

[76] Inventors: **Peter Blomdell**, Bjönbärsgatan 10, 412 67 Göteborg; **Rolf Agerbert**, Delsjövägen 3, 412 66 Göteborg, both of Sweden

[**] Term: **14 Years**

[21] Appl. No.: **62,650**

[22] Filed: **Nov. 21, 1996**

[51] **LOC (6) Cl. 06-01**

[52] **U.S. Cl. D6/356**

[58] **Field of Search** D6/334, 335, 336, D6/356, 367, 500, 501, 502; 297/216.1, 468

[56] **References Cited**

U.S. PATENT DOCUMENTS

- D. 273,540 4/1984 Wagner et al. D6/356
- D. 355,986 3/1995 Myers D6/356

- D. 371,465 7/1996 Stulik D6/356
- 4,019,776 4/1977 Takamatsu D6/502 X
- 5,362,132 11/1994 Griswold et al. D6/356 X

Primary Examiner—Gary D. Watson
Attorney, Agent, or Firm—Young & Thompson


[57] **CLAIM**

The ornamental design for a vehicle seat, as shown and described.

DESCRIPTION

FIG. 1 is a front, side and top perspective view of a vehicle seat showing our new design;
 FIG. 2 is a view similar to FIG. 1 but with a seat belt in an alternative position; and,
 FIG. 3 is a side and rear perspective view thereof.
 The portions of the vehicle seat not shown in the drawing form no part of the claimed design.
 The broken lines shown on the left side of the headrest in FIGS. 1 and 2 represent stitching.

1 Claim, 1 Drawing Sheet






FIG. 1




FIG. 2




FIG. 3