



US00D406998S

United States Patent [19]
Thomas

[11] Patent Number: Des. 406,998
[45] Date of Patent: **Mar. 23, 1999

[54] SHEARS

[75] Inventor: Dieter Thomas, Solingen, Germany

[73] Assignee: Zwilling J.A. Henckels AG, Germany

[**] Term: 14 Years

[21] Appl. No.: 85,374

[22] Filed: Mar. 12, 1998

[30] Foreign Application Priority Data

Oct. 30, 1997 [DE] Germany M 97 10 039.0

[51] LOC (6) Cl. 08-03

[52] U.S. Cl. D8/57; D8/107

[58] Field of Search D19/65, 72, 99,
D19/100; D8/57, 98; 30/28, 27, 29, 194,
252, 253, 254, 261, 262, 266, 118, 124,
123, 230, 232, 233; 7/131-135

[56] References Cited

U.S. PATENT DOCUMENTS

D. 212,273	9/1968	Sinko		D8/57 X
D. 231,186	4/1974	Laurenti		D8/57
D. 237,038	10/1975	Laurenti		D8/57
D. 242,425	11/1976	Backstrom		D8/57
D. 281,104	10/1985	Davison		D8/57 X
D. 296,757	7/1988	Strack		D8/57
D. 350,466	9/1994	Ramsey et al.		D8/57
1,645,981	10/1927	Benedict		30/254
2,965,967	12/1960	Wahl		30/254 X
3,750,282	8/1973	Eaton et al.		30/254
5,469,626	11/1995	Vogel et al.		30/266

Primary Examiner—Martie K. Holtje
Attorney, Agent, or Firm—Hill & Simpson

[57] CLAIM

The ornamental design for a pair of shears, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a first embodiment of a pair of shears of the present invention;

FIG. 2 is a side view taken from the left side of the shears of FIG. 1;
FIG. 3 is a side view taken from the right side of the shears of FIG. 1;
FIG. 4 is a rear elevational view of the shears of FIG. 1;
FIG. 5 is an end view of the end of the handle of the shears of FIG. 1;
FIG. 6 is an end view of the blade end of the shears of FIG. 1;
FIG. 7 is a front elevational view of a second embodiment of a pair of shears of the present invention;
FIG. 8 is a side view taken from the left side of the shears of FIG. 7;
FIG. 9 is a side view taken from the right side of the shears of FIG. 7;
FIG. 10 is a rear elevational view of the shears of FIG. 7;
FIG. 11 is an end view of the handle end of the shears of FIG. 7;
FIG. 12 is an end view of the blade end of the shears of FIG. 7;
FIG. 13 is a front elevational view of a third embodiment of a pair of shears of the present invention;
FIG. 14 is a side view taken from the left side of the shears of FIG. 13;
FIG. 15 is a side view taken from the right side of the shears of FIG. 13;
FIG. 16 is a rear elevational view of the shears of FIG. 13;
FIG. 17 is an end view of the handle end of the shears of FIG. 13;
FIG. 18 is an end view of the blade end of the shears of FIG. 13;
FIG. 19 is a front elevational view of a fourth embodiment of a pair of shears of the present invention;
FIG. 20 is a side view taken from the left side of the shears of FIG. 19;
FIG. 21 is a side view taken from the right side of the shears of FIG. 19;
FIG. 22 is a rear elevational view of the shears of FIG. 19;
FIG. 23 is an end view of the handle end of the shears of FIG. 19; and,
FIG. 24 is an end view of the blade end of the shears of FIG. 19.

1 Claim, 4 Drawing Sheets




Fig.1




Fig.2 Fig.3




Fig.4




Fig.5



Fig.6

Fig.7




Fig.8



Fig.9



Fig.10




Fig.11



Fig.12

Fig.13




Fig.14 Fig.15




Fig.16




Fig.17



Fig.18

Fig.19




Fig.20 Fig.21




Fig.22




Fig.23




Fig.24