



US00D408732S

**United States Patent** [19]  
**Gaffney et al.**

[11] **Patent Number: Des. 408,732**

[45] **Date of Patent: \*\*Apr. 27, 1999**

[54] **PACKAGE FOR BATTERIES**

[75] Inventors: **Robert C. Gaffney**, Sun Prairie;  
**Gerald A. Albright**, Middleton; **Larry K. Bauer**, Madison, all of Wis.

[73] Assignee: **Rayovac Corporation**, Madison, Wis.

[\*\*] Term: **14 Years**

[21] Appl. No.: **29/083,016**

[22] Filed: **Feb. 2, 1998**

[51] **LOC (6) Cl.** ..... **09-07**

[52] **U.S. Cl.** ..... **D9/415**

[58] **Field of Search** ..... D9/415, 418, 341,  
D9/337, 346, 456; 200/461-471, 806, 333,  
445, 495, 775-783, 303; 224/902

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

|            |         |                   |       |           |
|------------|---------|-------------------|-------|-----------|
| D. 222,581 | 11/1971 | Nakakuma          | ..... | D9/415    |
| D. 295,833 | 5/1988  | Roth              | ..... | D9/337    |
| D. 307,554 | 5/1990  | McAlister, Sr.    | ..... | D9/415    |
| D. 330,855 | 11/1992 | DeMcPoulos et al. | ..... | D9/341 X  |
| D. 393,799 | 4/1998  | Pope et al.       | ..... | D9/415    |
| D. 394,207 | 5/1998  | Waterbury et al.  | ..... | D9/415    |
| 4,896,770  | 1/1990  | Catrano et al.    | ..... | 206/461 X |
| 5,311,989  | 5/1994  | Ward et al.       | .     |           |
| 5,429,233  | 7/1995  | Juaristi          | ..... | 206/461 X |
| 5,462,161  | 10/1995 | Haaburda et al.   | ..... | 206/420 X |
| 5,586,657  | 12/1996 | Ward              | .     |           |
| 5,593,636  | 1/1997  | Dyboe et al.      | ..... | 206/464   |

**OTHER PUBLICATIONS**

“New PDQ Display,” Rayovac Corporation, Madison, Wisconsin. No date.

“Rayovac Maximum® Challenge Dangler,” Rayovac Corporation, Madison, Wisconsin no date.

*Primary Examiner*—Prabhakar Deshmukh  
*Attorney, Agent, or Firm*—Lathrop & Clark LLP

[57] **CLAIM**

The ornamental design for a package for batteries, as shown and described.

**DESCRIPTION**

FIG. 1 is a front isometric view of a package for batteries of this invention;

FIG. 2 is a left side elevational view thereof;

FIG. 3 is a right side elevational view thereof;

FIG. 4 is a front elevational view thereof;

FIG. 5 is a rear elevational view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a top plan view thereof;

FIG. 8 is a front elevational view of an alternative embodiment package for batteries of this invention, the rear elevational view being identical to FIG. 5;


FIG. 9 is a left side elevational view thereof;


FIG. 10 is a right side elevational view thereof;

FIG. 11 is a bottom plan view thereof; and,


FIG. 12 is a top plan view thereof.

**1 Claim, 3 Drawing Sheets**







*Fig. 1*




*Fig. 2*



*Fig. 3*



*Fig. 4*




*Fig. 5*




*Fig. 6*




*Fig. 7*




*Fig. 8*




*Fig. 9*



*Fig. 10*



*Fig. 11*



*Fig. 12*