US00D409630S

# United States Patent [19]

**Cornell et al.**

[11] **Patent Number: Des. 409,630**

[45] **Date of Patent: ** May 11, 1999**

[54] **CIRCLE CUTTER**

[75] Inventors: **Robert W. Cornell**, Schofield; **Randall J. Urness**, Plover, both of Wis.

[73] Assignee: **Fiskars Inc.**, Wausau, Wis.

[**] Term: **14 Years**

[21] Appl. No.: **29/082,874**

[22] Filed: **Jan. 30, 1998**

[51] **LOC (6) Cl.** ..... **15-09**

[52] **U.S. Cl.** ..... **D15/127**

[58] **Field of Search** ..... D15/127; D8/98; 30/319; 83/300, 304, 310, 456, 464, 490, 508.2, 565, 745; 266/58, 70; 408/102

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|---|---|---|---|
| 179,039 | 6/1876 | McAdams . | |
| 494,864 | 4/1893 | Huston . | |
| 572,320 | 12/1896 | Stuparich . | |
| 658,710 | 9/1900 | Forker . | |
| 658,711 | 9/1900 | Forker . | |
| 701,828 | 6/1902 | Arnold . | |
| 705,576 | 7/1902 | Forker . | |
| 742,047 | 10/1903 | Moehle . | |
| 1,391,530 | 9/1921 | Diego . | |
| 3,621,574 | 11/1971 | Yanke et al. . | |
| 4,222,169 | 9/1980 | Lockwood . | |
| 4,773,798 | 9/1988 | Gaster et al. . | |
| 4,782,730 | 11/1988 | Picone et al. . | |
| 5,038,651 | 8/1991 | Burdick | 83/565 |

OTHER PUBLICATIONS

Packaging for NY Cutters, Part No's. C–2500P and C–1500P, NT Incorporated.

*Primary Examiner*—Antoine Duval Davis
*Attorney, Agent, or Firm*—Foley & Lardner

[57] **CLAIM**

The ornamental design of a circle cutter, as shown and described.

**DESCRIPTION**

FIG. **1** is an isometric view of a circle cutter having a radially positionable arm;

FIG. **2** is a top plan view of the circle cutter shown in FIG. **1**;

FIG. **3** is a left side elevation view of the circle cutter shown in FIG. **1** with the positionable arm in a retracted position, the opposite side of the circle cutter being the same as that shown in FIG. **3**;

FIG. **4** is a front end elevation view of the circle cutter shown in FIG. **1**;

FIG. **5** is a rear end elevation of the circle cutter shown in FIG. **1**;

FIG. **6** is a bottom plan view of the circle cutter shown in FIG. **1** with the positionable arm in a retracted position;

FIG. **7** is a right side elevation of the circle cutter shown in FIG. **1** with the positionable arm in an extended position, the opposite side of the circle cutter being the same as that shown in FIG. **7**;

FIG. **8** is an isometric view of the circle cutter of FIG. **1** with only the palm pad and a portion of the housing in solid lines;

FIG. **9** is a top plan view of the circle cutter shown in FIG. **8**;

FIG. **10** is a left side elevation view of the circle cutter shown in FIG. **8**, the opposite side of the circle cutter being the same as that shown in FIG. **10**;

FIG. **11** is a front end elevation view of the circle cutter shown in FIG. **8**;

FIG. **12** is a rear end elevation view of the circle cutter shown in FIG. **8**; and,

FIG. **13** is a bottom plan view of the circle cutter shown in FIG. **8**.

The broken lines showing portions of the circle cutter in the FIG's. are for illustrative purposes only and form no part of the claimed design.

**1 Claim, 4 Drawing Sheets**





FIG. 1



FIG. 2



FIG. 3

FIG. 4



FIG. 5



FIG. 6



FIG. 7



FIG. 8





FIG. 9



FIG. 10



FIG. 11



FIG. 12



FIG. 13