



US00D411313S

United States Patent [19]
Azar

[11] **Patent Number:** **Des. 411,313**
[45] **Date of Patent:** **** Jun. 22, 1999**

[54] **ANGULATED INTERLOCKING BUILDING ELEMENT**

[76] **Inventor:** **Edward Azar**, 3265 Blairwood Court,
Windsor, Ontario, Canada, N8W 5M7

[**] **Term:** **14 Years**

[21] **Appl. No.:** **29/067,683**

[22] **Filed:** **Mar. 11, 1997**

[30] **Foreign Application Priority Data**

Sep. 12, 1996 [CA] Canada 1996-2033

[51] **LOC (6) Cl.** **21-01**

[52] **U.S. Cl.** **D25/113; D25/151**

[58] **Field of Search** D25/113-118,
D25/151, 138; D21/484-505; 446/85, 110,
124, 125; 52/311.2, 596; 404/17, 34, 40-45

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 35,691	2/1902	Watts, Jr. .	
D. 226,016	1/1973	Podell	D21/503
D. 272,474	1/1984	Belgiojoso	D25/138
779,636	1/1905	Dickey .	
1,002,979	9/1911	Fee .	
3,310,906	3/1967	Glukes .	
3,931,700	1/1976	Scanni et al.	52/590
4,262,467	4/1981	Faisant et al.	52/311.2
4,973,192	11/1990	Hair	404/41
5,575,125	11/1996	Lalvani	52/311.2
5,775,040	7/1998	Lalvani	52/311.2

OTHER PUBLICATIONS

Sweet's Homebuilding & Remodeling Cat. p. A135. 1994.

Primary Examiner—Raphael Barkai
Attorney, Agent, or Firm—Anthony J. Casella; Gerald E. Hespos; Ludomir A. Budzyn

[57] **CLAIM**

The ornamental design of an angulated interlocking building element, as shown and described.

DESCRIPTION

FIG. 1 is a top-front perspective view of an angulated interlocking building element in accordance with my design, and showing the building element having a thickness suitable for a vinyl floor tile;

FIG. 2 is a top plan view of the angulated interlocking building element shown in FIG. 1, with the bottom plan view being substantially identical;

FIG. 3 is a front elevational view of the angulated interlocking building element shown in FIG. 1;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is a side elevational view as viewed from the right side of FIG. 2;

FIG. 6 is a side elevational view as viewed from the left side of FIG. 2;

FIG. 7 is a top-front perspective view of a modified embodiment of the design shown in FIGS. 1-6 and having a thickness suitable for a ceramic tile;

FIG. 8 is a top plan view of the angulated interlocking building element shown in FIG. 7, with the bottom plan view being substantially identical;


FIG. 9 is a front elevational view of the angulated interlocking building element shown in FIG. 7;

FIG. 10 is a rear elevational view thereof;

FIG. 11 is a side elevational view as viewed from the right side of FIG. 8; and

FIG. 12 is a side elevational view as viewed from the left side of FIG. 8.

1 Claim, 1 Drawing Sheet






FIG. 1



FIG. 3




FIG. 2



FIG. 4



FIG. 5



FIG. 6




FIG. 7



FIG. 9




FIG. 8



FIG. 10



FIG. 11



FIG. 12