



US00D413646S

# United States Patent [19] Edgar

[11] Patent Number: Des. 413,646

[45] Date of Patent: \*\* Sep. 7, 1999

[54] MOUNT FOR SECURING A SIGHTING LIGHT TO A FIREARM

[76] Inventor: Mark S. Edgar, P.O. Box 399, Clarkston, Wash. 99403

[\*\*] Term: 14 Years

[21] Appl. No.: 29/096,258

[22] Filed: Nov. 9, 1998

### Related U.S. Application Data

[63] Continuation-in-part of application No. 29/083,659, Feb. 13, 1998.

[51] LOC (6) Cl. .... 22-01

[52] U.S. Cl. .... D22/110; D22/108; D22/109

[58] Field of Search ..... D22/100, 108, D22/109, 110, 199; 33/245, 246, 247, 248, 249, 250; 42/100, 101, 103; 362/110, 113, 114

### [56] References Cited

#### U.S. PATENT DOCUMENTS

D. 203,508	1/1966	Hansen	.....	D22/110
D. 270,748	9/1983	Bechtel	.....	D22/110
D. 281,804	12/1985	Bechtel	.....	D22/110
D. 286,424	10/1986	Ekstrand	.....	362/110
D. 331,442	12/1992	Bechtel	.....	D22/110
D. 331,443	12/1992	Bechtel	.....	D22/110
D. 365,621	12/1995	Coste	.....	D22/109
D. 394,096	5/1998	Edgar	.....	D22/110
894,306	7/1908	Wright	.	
1,215,171	2/1917	Lewis	.	
1,535,459	4/1925	Fredrickson	.	
2,043,430	6/1936	Doe	.....	33/247

2,385,649	9/1945	Prideaux	.....	42/100
2,529,057	11/1950	Teffault	.....	362/110
2,546,242	3/1951	Stinson	.....	240/6.41
3,381,924	5/1968	Gagnier	.....	33/247
3,556,666	1/1971	Lichtenstern	.....	33/245
3,992,782	11/1976	Richert	.....	33/246
4,562,658	1/1986	Govett	.....	33/247 X
4,742,635	5/1988	Ruger et al.	.....	33/245 X
4,777,754	10/1988	Reynolds, Jr.	.....	42/103
4,890,407	1/1990	Nichols	.....	42/103
4,894,941	1/1990	Karow, Jr.	.....	42/103
5,042,186	8/1991	Bechtel	.....	42/103
5,107,612	4/1992	Bechtel	.....	42/103
5,581,898	12/1996	Thummel	.....	42/103

Primary Examiner—B. J. Bullock  
Assistant Examiner—Monica A. Weingart  
Attorney, Agent, or Firm—Wells, St. John, Roberts, Gregory & Matkin P.S.


### [57] CLAIM

The ornamental design for a mount for securing a sighting light to a firearm, as shown and described.

### DESCRIPTION

FIG. 1 is a perspective view of a mount for securing a sighting light to a firearm showing my new design;  
FIG. 2 is a reduced front elevation view thereof;  
FIG. 3 is a rear elevation view thereof;  
FIG. 4 is a left end elevation thereof as viewed from the left in FIG. 2;  
FIG. 5 is a right end elevation thereof as viewed from the right in FIG. 2;  
FIG. 6 is a top plan view thereof; and,  
FIG. 7 is a bottom plan view thereof.

1 Claim, 2 Drawing Sheets






FIG. 1




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6