



US00D413803S

United States Patent [19]

[11] **Patent Number: Des. 413,803**

Albright et al.

[45] **Date of Patent: ** Sep. 14, 1999**

[54] **BATTERY PACKAGE**

[75] Inventors: **Gerald A. Albright**, Middleton; **Robert C. Gaffney**, Sun Prairie; **Richard L. Pedracine**, Madison; **Ross Mack**, Dane; **Ron Hellenbrand**, Middleton, all of Wis.

[73] Assignee: **Rayovac Corporaion**, Madison, Wis.

[**] Term: **14 Years**

[21] Appl. No.: **29/094,324**

[22] Filed: **Sep. 30, 1998**

[51] **LOC (6) Cl.** **09-07**

[52] **U.S. Cl.** **D9/423; D9/425**

[58] **Field of Search** D9/420-425, 428, D9/432, 414, 337; 206/327, 703, 704, 705, 461-471, 508; 220/334, 337, 669-675; 229/406

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|------------|---------|---------------------|-----------|
| D. 222,581 | 11/1971 | Nakakuma et al. . | |
| D. 295,833 | 5/1988 | Roth . | |
| D. 307,554 | 5/1990 | McAllister, Sr. . | |
| D. 330,855 | 11/1992 | Demopoulos et al. . | |
| D. 339,744 | 9/1993 | Seppala | D9/425 |
| D. 363,879 | 11/1995 | Krupa et al. | D9/423 |
| D. 393,799 | 4/1998 | Pope et al. . | |
| D. 394,207 | 5/1998 | Waterbury et al. . | |
| 4,696,402 | 9/1987 | Harmon et al. . | |
| 4,848,568 | 7/1989 | Eckelman | 206/705 |
| 4,896,770 | 1/1990 | Calcerano et al. . | |
| 4,958,731 | 9/1990 | Calcerano | 206/705 |
| 4,971,197 | 11/1990 | Worley | 206/705 |
| 4,974,738 | 12/1990 | Kidd et al. | 229/406 X |

(List continued on next page.)

OTHER PUBLICATIONS

Ultra Fresh, p. 16, Mar. 1995.
“New PDQ Display”—Rayovac Corporation, Madison, Wisconsin—1998.

“Rayovac Maximum® Challenge Dangler”—Rayovac Corporation, Madison, Wisconsin, no date known.

“New Maximum™ Alkaline 16 Pack”—Rayovac Corporation, Madison, Wisconsin—1997.

“America’s #1 Heavy Duty Battery”—Rayovac Corporation, Madison, Wisconsin—1998.

U.S. Patent Application No. 29/086,883, filed Apr. 22, 1998.

U.S. Patent Application No. 29/086,884, filed Apr. 22, 1998.

Primary Examiner—Prabhakar Deshmukh

[57] **CLAIM**

The ornamental design for a battery package, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a battery package showing our new design; shown in an open position;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a rear elevational view thereof;

FIG. 4 is a right side elevational view thereof, the left side elevational view being a mirror image thereof;

FIG. 5 is a top plan view; and

FIG. 6 is a bottom plan view.

FIG. 7 is a perspective view of a second embodiment of a battery package; shown in an open position;

FIG. 8 is a front elevational view thereof;

FIG. 9 is a rear elevational view thereof;

FIG. 10 is a right side elevational view thereof, the left side elevational view being a mirror image thereof;

FIG. 11 is a top plan view; and

FIG. 12 is a bottom plan view.

FIG. 13 is a perspective view of a third embodiment of a battery package; shown in an open position;

FIG. 14 is a front elevational view thereof;

FIG. 15 is a rear elevational view thereof;


FIG. 16 is a right side elevational view thereof, the left side elevational view being a mirror image thereof;

FIG. 17 is a top plan view; and,

FIG. 18 is a bottom plan view.

The broken lines showing of the batteries is for illustrative purpose only and forms no part the claimed design.

1 Claim, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18