



US00D416427S

# United States Patent [19]

Pecora et al.

[11] Patent Number: Des. 416,427

[45] Date of Patent: \*\* Nov. 16, 1999

## [54] CUSHIONED STRESS RELIEVING DEVICE

[76] Inventors: **Damiano C. Pecora**, 80 English Street, Brampton, Ontario, Canada, L6X 2P6;  
**Cosma G. Pecora**, 47 Raymond Rd., Woodbridge, Ontario, Canada, L4L 2K9

[\*\*] Term: **14 Years**

[21] Appl. No.: **29/097,676**

[22] Filed: **Dec. 11, 1998**

[51] **LOC (6) Cl.** ..... **06-09**

[52] **U.S. Cl.** ..... **D6/601; D24/211; D24/214**

[58] **Field of Search** ..... D6/595, 596, 597, D6/601, 604; 5/630, 636, 648, 652, 653, 654, 655, 655.9, 657.5, 646; D24/200, 211, 214; 601/115, 119, 120, 121

## [56] References Cited

### U.S. PATENT DOCUMENTS

D. 257,200	10/1980	LaRocca	.....	D6/601
D. 384,158	9/1997	Kain	.....	D24/215
D. 388,878	1/1998	Darula	.....	D24/200
718,594	1/1903	Bailey	.	
1,933,989	11/1933	McCullough	.	
3,899,797	8/1975	Gunst	.....	5/655.3
4,471,768	9/1984	Ciullo	.	
4,493,315	1/1985	Iwahashi	.	
4,944,747	7/1990	Newth et al.	.	
5,545,199	8/1996	Hudson	.....	607/109
5,643,182	7/1997	Engel	.....	601/119

### FOREIGN PATENT DOCUMENTS

1648-407A 5/1991 U.S.S.R. .

*Primary Examiner*—Janice E. Seeger  
*Attorney, Agent, or Firm*—Barrigar & Moss


## [57] CLAIM

The ornamental design for cushioned stress relieving device, as shown and described.

## DESCRIPTION

FIG. 1 is a perspective view of a first variant of the cushioned stress relieving device showing the device in a straight position;  
 FIG. 2 is a side view of the stress relieving device of FIG. 1;  
 FIG. 3 is a top view of the stress relieving device of FIG. 1;  
 FIG. 4 is an end view showing one end of the stress relieving device of FIG. 1;  
 FIG. 5 is another end view showing the opposite end of the stress relieving device of FIG. 1;  
 FIG. 6 is another perspective view of the stress relieving device of FIG. 1 showing the device in a bent position;  
 FIG. 7 is a top view of the stress relieving device of FIG. 6;  
 FIG. 8 is a side view of the stress relieving device of FIG. 6;  
 FIG. 9 is an opposite side view of the stress relieving device of FIG. 6;  
 FIG. 10 is a perspective view of a second variant of the stress relieving device showing the device in a straight position,  
 FIG. 11 is a side view of the stress relieving device of FIG. 10;  
 FIG. 12 is an end view of the stress relieving device of FIG. 10;  
 FIG. 13 is another perspective view of the stress relieving device of FIG. 10, showing the device in a bent position;  
 FIG. 14 is a top view of the stress relieving device of FIG. 13;  
 FIG. 15 is a side view of the stress relieving device of FIG. 13; and,  
 FIG. 16 is an opposite side view of the stress relieving device of FIG. 13.

**1 Claim, 8 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6






FIG. 7




FIG. 8



FIG. 9




FIG.10



FIG. 11




FIG. 12




FIG. 13






FIG.14




FIG.15




FIG.16