



US00D419084S

# United States Patent [19]

[11] **Patent Number: Des. 419,084**

**Boehringer et al.**

[45] **Date of Patent: \*\* Jan. 18, 2000**

[54] **GAUGE**

4,182,175	1/1980	Boehringer .	
4,231,375	11/1980	Boehringer .	
4,257,279	3/1981	Marx .....	73/861.57
4,934,187	6/1990	Woltman .....	73/198

[75] Inventors: **John R. Boehringer**, Wynnewood;  
**John Karpowicz**, Chester Springs;  
**Michael I. Hegedus**, Royersford, all of Pa.

*Primary Examiner*—Antoine Duval Davis  
*Attorney, Agent, or Firm*—Paul & Paul

[73] Assignee: **Boehringer Laboratories, Inc.**,  
Norristown, Pa.

[57] **CLAIM**

[\*\*] Term: **14 Years**

The ornamental design for the gauge, as shown and described.

[21] Appl. No.: **29/093,064**

**DESCRIPTION**

[22] Filed: **Sep. 2, 1998**

FIG. 1 is a front view of the gauge.  
 FIG. 2 is a top view thereof.  
 FIG. 3 is a right side view thereof. The left side view is a mirror image of the view of FIG. 3; and,  
 FIG. 4 is a perspective view of the gauge.  
 The broken lines indicate the environment of the design of the present invention; namely of that portion of the gauge which does not form part of design.


[51] **LOC (7) Cl.** ..... **10-04**  
 [52] **U.S. Cl.** ..... **D10/85**  
 [58] **Field of Search** ..... D10/85; 78/861.44,  
 78/861.79, 204.71, 861.52, 861.56, 1.34,  
 162; 600/513, 538, 539, 541

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

D. 221,476 8/1971 Martin ..... D10/85

**1 Claim, 1 Drawing Sheet**






FIG. 2




FIG. 1



FIG. 3




FIG. 4