



US00D419747S

United States Patent [19]

[11] Patent Number: Des. 419,747

Noblet et al.

[45] Date of Patent: ** Jan. 25, 2000

[54] CLUSTER BOX UNIT

[75] Inventors: C. Dale Noblet, San Bernardino, Calif.;
Stephen R. Packer, Las Vegas, Nev.

[73] Assignee: Can-Am Marketing Corporation,
Inc., Las Vegas, Nev.

[**] Term: 14 Years

[21] Appl. No.: 29/102,276

[22] Filed: Mar. 22, 1999

[51] LOC (7) Cl. 99-00

[52] U.S. Cl. D99/28; D99/32

[58] Field of Search D99/28, 29, 31,
D99/32, 33; 232/17, 24, 25, 27; 109/53;
312/215, 198

4,725,084	2/1988	Catricola .	
4,751,834	1/1988	Beck .	
4,836,352	6/1989	Tateno et al.	194/215
4,861,082	8/1989	Priola et al. .	
4,865,248	9/1989	Barth	232/24
5,074,606	12/1991	Priola et al. .	
5,395,145	3/1995	Allenbaugh .	
5,406,814	4/1995	Zeager et al. .	
5,415,020	5/1995	Allenbaugh .	
5,472,378	12/1995	Skoff .	
5,520,450	5/1996	Colson, Jr. et al.	312/215
5,566,995	10/1996	Jagiela .	
5,771,720	6/1998	Levenson .	
5,820,019	10/1998	Spitale	312/215

Primary Examiner—Paula A. Mortimer
Attorney, Agent, or Firm—Cislo & Thomas LLP

[57] CLAIM

The ornamental design for an cluster box unit, as shown and described.

[56] References Cited

U.S. PATENT DOCUMENTS

D. 293,154	12/1987	McKellar	D99/28
D. 315,996	4/1991	Barth et al.	D99/28
D. 326,757	6/1992	Ullman	D99/29
D. 374,966	10/1996	Matassa	D99/28
894,577	7/1908	Bessnor	D99/29
2,049,796	8/1936	Barry .	
2,470,799	5/1949	Ames .	
2,495,537	1/1950	Mousel .	
2,529,994	11/1950	Brezek .	
2,556,464	6/1951	Brezek .	
2,557,908	6/1951	Cross .	
2,576,503	11/1951	Dean .	
2,731,098	1/1956	Saives .	
2,779,164	1/1957	Doane .	
2,787,206	4/1957	Dustman .	
2,918,319	12/1959	Richardson .	
3,405,962	10/1968	Sushan .	
3,592,498	7/1971	Raccuglia, Sr. .	
3,784,089	1/1974	Koch	232/24
4,072,487	2/1978	Irwin .	
4,257,633	3/1981	Rosenberg .	
4,345,787	8/1982	Dabrowski .	
4,350,084	9/1982	Azzola .	
4,557,416	12/1985	Stahl et al.	232/24

DESCRIPTION

FIG. 1 is a front plan view of the cluster box unit (CBU) of the present invention showing a pedestal, the locks, and adjoining mail box slot door structures for the CBU in phantom;

FIG. 2 is a rear view of the CBU of FIG. 1;

FIG. 3 is a right side view of the CBU of FIG. 1. The left side view is a mirror image of the right side view;

FIG. 4 is a top plan view of the CBU of FIG. 1;


FIG. 5 is a bottom plan view of the CBU of FIG. 1;

FIG. 6 is a top right side perspective view of the front of the CBU of FIG. 1; and,

FIG. 7 is a front perspective view of the CBU of FIG. 1 showing the double door in an open and ajar position, respectively. The central sliding linkage, the door pins, and various door locks are shown in phantom.

The broken line showing of pedestal in FIGS. 1,2,3,5,6,7, the locks and adjoining mail box slot in FIGS. 1,6, and 7, and the linkage, the door pins, and various door locks in FIG. 7 is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7