United States Patent [19] Riley

US00D420620S Des. 420,620 **Patent Number:** [11] Date of Patent: ****** Feb. 15, 2000 [45]

LANYARD BUCKLE [54]

Phil Riley, 6024 SW. Jean Rd. #175-F, [76] Inventor: Lake Oswego, Oreg. 97035

14 Years [**] Term:

- Appl. No.: 29/101,244 [21]
- Mar. 1, 1999 [22] Filed:
- LOC (7) Cl. 02-07 [51]

FIG. 2 is a top plan view;

FIG. 3 is a front elevational view;

FIG. 4 is a right side elevational view, the left side view being a mirror image;

FIG. 5 is a bottom plan view;

FIG. 6 is a perspective view of the male portion of the buckle, the female portion has been removed for ease of illustration;

FIG. 7 is a top plan view of FIG. 6;

[52] [58] D11/216, 218; D8/383, 358; 24/96, 97, 200, 196, 197, 164, 616, 625, 633; 224/257, 258, 265; D21/801

[56] **References Cited** U.S. PATENT DOCUMENTS

D. 303,233	9/1989	Jang D) 11/216
D. 320,178	9/1991	Kasai D	011/218
D. 349,664	8/1994	Ueno D	011/218
D. 381,936	8/1997	Airscher D	D 11/216

Primary Examiner—Ralf Seifert

[57] CLAIM

The ornamental design for a lanyard buckle, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a lanyard buckle showing my new design;

FIG. 8 is a front elevational view of FIG. 6;

FIG. 9 is a right side elevational view of FIG. 6, the left side view being a mirror image;

FIG. 10 is a bottom plan view of FIG. 6;

FIG. 11 is a perspective view of the female portion of the buckle, the male portion being removed for ease of illustration;

FIG. 12 is a top plan view of FIG. 11;

FIG. 13 is a front elevational view of FIG. 11;

FIG. 14 is a right side elevational view of FIG. 11, the left side view being a mirror image; and,

FIG. 15 is a bottom plan view of FIG. 11.

The broken line showing of portions of the lanyard in FIGS. 1, 3, 4, 6, 8, 9, 11, 13 and 14 are for illustrative purposes only and form no part of the claimed design.

1 Claim, 3 Drawing Sheets



U.S. Patent Feb. 15, 2000 Sheet 1 of 3 Des. 420,620





Des. 420,620 **U.S. Patent** Feb. 15, 2000 Sheet 2 of 3

FIG. 6





FIG. 7



FIG. 8 FIG. 9







U.S. Patent Feb. 15, 2000 Sheet 3 of 3 Des. 420,620

FIG. 11 FIG. 12





FIG. 13 FIG. 14







FIG. 15

