



US00D420988S

# United States Patent [19]

Yamano et al.

[11] **Patent Number: Des. 420,988**

[45] **Date of Patent: \*\* Feb. 22, 2000**

[54] **IMAGE INPUT DEVICE**

[75] Inventors: **Hirokazu Yamano; Teruo Baba**, both of Suwa, Japan

[73] Assignee: **Seiko Epson Corporation**, Tokyo, Japan

[\*\*] Term: **14 Years**

[21] Appl. No.: **29/100,703**

[22] Filed: **Feb. 16, 1999**

### [30] Foreign Application Priority Data

Aug. 17, 1998 [JP] Japan ..... 10-23490

[51] **LOC (7) Cl.** ..... **14-02**

[52] **U.S. Cl.** ..... **D14/107**

[58] **Field of Search** ..... D14/100, 106, D14/107-109, 118, 105; D18/36, 37, 39; 235/454, 470, 380, 382, 382.5; 250/556; 355/64, 65, 75, 81

### [56] References Cited

#### U.S. PATENT DOCUMENTS

D. 388,733 1/1998 Chang et al. .... D14/107  
D. 391,930 3/1998 Cheng-Yung ..... D14/107

*Primary Examiner*—Freda Nunn  
*Attorney, Agent, or Firm*—Stroock & Stroock & Lavan LLP

### [57] CLAIM

The ornamental design for an image input device, as shown and described.

### DESCRIPTION

FIG. 1 is a perspective view of an image input device in accordance with the present invention;

FIG. 2 is a top plan view of the image input device of FIG. 1;

FIG. 3 is a front elevational view of the image input device of FIG. 1;

FIG. 4 is a left side elevational view of the image input device of FIG. 1;



FIG. 5 is a right side elevational view of the image input device of FIG. 1;

FIG. 6 is a rear elevational view of the image input device of FIG. 1;


FIG. 7 is a bottom plan view of the image input device of FIG. 1; and,

FIG. 8 is a perspective view of the image input device of FIG. 1 with the top cover in an open position.


**1 Claim, 3 Drawing Sheets**



*FIG. 1*




*FIG. 2*



*FIG. 3*




*FIG. 4*



*FIG. 5*



*FIG. 6*






FIG. 7




FIG. 8