

US00D421239S

United States Patent [19]
Shillingburg

[11] **Patent Number: Des. 421,239**
[45] **Date of Patent: ** Feb. 29, 2000**

[54] **CONVERTIBLE BELT/STRAP BUCKLE**

[76] Inventor: **Craig Paul Shillingburg**, 1513 East St., Golden, Colo. 80401

[**] Term: **14 Years**

[21] Appl. No.: **29/087,250**

[22] Filed: **Apr. 29, 1998**

[51] **LOC (6) Cl. 02-07**

[52] **U.S. Cl. D11/217**

[58] **Field of Search D11/1-4, 200, D11/201, 217, 218, 219, 223, 224, 232, 233, 238, 32, 44, 96; D2/631, 632, 627; 24/163 R; 63/15**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 127,930	6/1941	Duvalet	D11/32
D. 135,206	3/1943	Mynors	D2/632
D. 159,115	6/1950	Weinberg	D11/44
D. 177,155	3/1956	Tapp	D11/96
D. 279,141	6/1985	Poland	D2/632
D. 370,585	6/1996	Faithfull	D2/631
D. 389,287	1/1998	Vanwinkle	D2/627
2,287,451	6/1942	Reiter	63/15

Primary Examiner—Ralf Seifert

[57] **CLAIM**

The ornamental design for a convertible belt/strap buckle, as shown.

DESCRIPTION

FIG. 1 is an isometric, front view of the convertible belt/strap buckle with the two parts clasped together.

FIG. 2 is a front view of the buckle system clasped together.

FIG. 3 is a bottom view of the buckle system clasped together.

FIG. 4 is a left side view that shows the male buckle part inserted into the female part.

FIG. 5 is an isometric, rear view of the buckle system with the two parts clasped together.

FIG. 6 is the rear view of the buckle system clasped together.

FIG. 7 is a top view that shows the male buckle part inserted into the female part.

FIG. 8 is a right side view that shows the male buckle part inserted into the female part.

FIG. 9 is an isometric view of the female buckle part looking down into the clip tab slot.

FIG. 10 is the back view of the female buckle part.

FIG. 11 is the front view of the female buckle part.

FIG. 12 is the top side view of the female buckle part.

FIG. 13 is the left end view of the female buckle part.

FIG. 14 is the bottom side view of the female buckle part.

FIG. 15 is the right end view of the female buckle part.

FIG. 16 is an isometric view of the male buckle part looking at the tap on its underside.

FIG. 17 is the back view of the male buckle part.

FIG. 18 is the front view of the male buckle part.


FIG. 19 is the top side view of the male buckle part.

FIG. 20 is the right end view of the male buckle part.

FIG. 21 is the bottom side view of the male buckle part; and,

FIG. 22 is the left end view of the male buckle part.

1 Claim, 4 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18



Fig. 19



Fig. 20



Fig. 21




Fig. 22