

US00D425489S

United States Patent [19]
Sacco et al.

[11] **Patent Number: Des. 425,489**
[45] **Date of Patent: ** May 23, 2000**

[54] **SURFACE CONFIGURATION OF ADJUSTMENT DEVICE**

[75] Inventors: **Bruno Sacco; Harald Leschke**, both of Sindelfingen, Germany; **Olivier Boulay**, Tokyo, Japan; **Shuichi Yamashita**, Yokohama, Japan; **Anthony Lo**, Tokyo, Japan

[73] Assignee: **DaimlerChrysler AG**, Germany

[**] Term: **14 Years**

[21] Appl. No.: **29/092,460**

[22] Filed: **Aug. 19, 1998**

[51] **LOC (7) Cl. 13-03**

[52] **U.S. Cl. D13/162**

[58] **Field of Search D13/162, 164, D13/169, 171; D12/192, 317; 200/5 R, 6 R, 314, 315, 339; 174/52.1**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 328,064	7/1992	Ahmed et al.	D13/162
D. 338,191	8/1993	Ahmed et al.	D13/162
3,135,839	6/1964	Colautti et al.	200/5 R
5,384,440	1/1995	Wnuk et al.	200/5 R
5,668,357	9/1997	Takiguchi et al.	200/5 R
5,866,862	2/1999	Riffil et al.	200/5 R

Primary Examiner—Adir Aronovich
Attorney, Agent, or Firm—Evenson, McKeown, Edwards & Lenahan, P.L.L.C.

[57] **CLAIM**

The ornamental design for a surface configuration of adjustment device, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a first embodiment of a surface configuration of adjustment device according to our novel design;

FIG. 2 is an enlarged front view of the first embodiment of the surface configuration of adjustment device according to our novel design;

FIG. 3 is a top view of the first embodiment of the surface configuration of adjustment device according to our novel design;

FIG. 4 is a front right perspective view of the first embodiment of the surface configuration of adjustment device according to our novel design;

FIG. 5 is a front view of a second embodiment of the surface configuration of adjustment device according to our novel design;


FIG. 6 is an enlarged front view of the second embodiment of the surface configuration of adjustment device according to our novel design;

FIG. 7 is a front right perspective view of the second embodiment of the surface configuration of adjustment device; and,

FIG. 8 is a front right perspective view of the second embodiment of the surface configuration of adjustment device according to our novel design.

The drawings and descriptions represent the adjustable device for the interior of the right side of a vehicle.

1 Claim, 4 Drawing Sheets






FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8