

US00D425706S

Patent Number:

Date of Patent:

Des. 425,706

** May 30, 2000

United States Patent [19]

Calderone

[54] COMBINED SHOESHINE PAD AND CONTAINER

[76] Inventor: Joseph Augustus Calderone, 40

Deanbank Drive, Thornhill Ontario,

Canada, L3T 6J3

[**] Term: 14 Years

[21] Appl. No.: 29/080,648

[22] Filed: Dec. 12, 1997

[52] **U.S. Cl.** **D4/116**; D3/200; D4/137; D9/307

37–38, 126–127, 130; D3/200; D9/307, 338; 206/15.2

[56] References Cited

U.S. PATENT DOCUMENTS

D. 150,218	7/1948	Fournier.
D. 189,266	11/1960	Harris D4/116
D. 264,364	5/1982	Pazurek .
D. 291,022	7/1987	Erickson.
D. 292,753	11/1987	Clayton et al
D. 320,311	10/1991	Kuhn.
D. 327,775	7/1992	Turner.
D. 329,485	9/1992	Hollinger.
D. 350,630	9/1994	Smith.
D. 357,500	4/1995	Mutterperl D21/317 X
D. 358,324	5/1995	Mitchell .
D. 390,778	2/1998	Lee
2,223,343	12/1940	Grant
2,840,842	7/1958	Kaheny 15/104.94
3,006,023	10/1961	Worthington 15/104.98
3,015,120	1/1962	Anderson .
4,339,062	7/1982	Witt, Jr
5,339,486	8/1994	Persic, Jr

Primary Examiner—Alan P. Douglas Assistant Examiner—Lavone D. Tabor



[11]

[45]

The ornamental design for a combined shoeshine pad and container, as shown.

DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of my design in the closed position;

FIG. 2 is a side view of a first embodiment of my design in the closed position;

FIG. 3 is a top view of a first embodiment of my design in the closed position;

FIG. 4 is a bottom view of a first embodiment of my design in the closed position;

FIG. 5 is a perspective view of a first embodiment of my design in the open position;

FIG. 6 is a side view of a first embodiment of my design in the open position;

FIG. 7 is a top view of a first embodiment of my design in the open position;

FIG. 8 is a bottom view of a first embodiment of my design in the open position;

FIG. 9 is a perspective view of a second embodiment of my design in the closed position;

FIG. 10 is a side view of a second embodiment of my design in the closed position;

FIG. 11 is a top view of a second embodiment of my design in the closed position;

FIG. 12 is a bottom view of a second embodiment of my design in the closed position;

FIG. 13 is a further side view of a second embodiment of my design in the closed position;

FIG. 14 is a perspective view of a second embodiment of my design in the open position;

FIG. 15 is a side view of a second embodiment of my design in the open position;


FIG. 16 is a top view of a second embodiment of my design in the open position;


FIG. 17 is a bottom view of a second embodiment of my design in the open position;


FIG. 18 is a perspective view of a third embodiment of my design in the closed position;

FIG. 19 is a side view of a third embodiment of my design in the closed position;

FIG. 20 is a top view of a third embodiment of my design in the closed position;










- FIG. 21 is a bottom view of a third embodiment of my design in the closed position;
- FIG. 22 is a further side view of a third embodiment of my design in the closed position;
- FIG. 23 is a perspective view of a third embodiment of my design in the open position;
- FIG. 24 is a side view of a third embodiment of my design in the open position;
- FIG. 25 is a top view of a third embodiment of my design in the open position;
- FIG. 26 is a bottom view of a third embodiment of my design in the open position;
- FIG. 27 is a perspective view of a fourth embodiment of my design in the closed position;
- FIG. 28 is a side view of a fourth embodiment of my design in the closed position;
- FIG. 29 is a top view of a fourth embodiment of my design in the closed position;
- FIG. 30 is a bottom view of a fourth embodiment of my design in the closed position;
- FIG. 31 is a further side view of a fourth embodiment of my design in the closed position;
- FIG. 32 is a perspective view of a fourth embodiment of my design in the open position;
- FIG. 33 is a side view of a fourth embodiment of my design in the open position;


- FIG. 34 is a top view of a fourth embodiment of my design in the open position;
- FIG. 35 is a bottom view of a fourth embodiment of my design in the open position;
- FIG. 36 is a perspective view of a fifth embodiment of my design in the closed position;
- FIG. 37 is a side view of a fifth embodiment of my design in the closed position;
- FIG. 38 is a top view of a fifth embodiment of my design in the closed position;
- FIG. 39 is a bottom view of a fifth embodiment of my design in the closed position;
- FIG. 40 is a further side view of a fifth embodiment of my design in the closed position;
- FIG. 41 is a perspective view of a fifth embodiment of my design in the open position;
- FIG. 42 is a side view of a fifth embodiment of my design in the open position;
- FIG. 43 is a top view of a fifth embodiment of my design in the open position; and,
- FIG. 44 is a bottom view of a fifth embodiment of my design in the open position.


1 Claim, 10 Drawing Sheets































May 30, 2000








FIG. 19








U.S. Patent May 30, 2000 Sheet 7 of 10 Des. 425,706














U.S. Patent Des. 425,706 **Sheet 10 of 10** May 30, 2000 FIG. 41 FIG. 43 FIG. 44