

US00D428373S

United States Patent [19]

Todd et al.

[54] COMBINED REARVIEW MIRROR AND NINE PIXEL SIGNALLING INDICATOR

[75] Inventors: Daniel R. Todd; Daniel J. Mathieu;

Allen A. Bukosky; Michael J. Musiel,

all of Sheboygan, Wis.

[73] Assignee: K. W. Muth Company, Inc.,

Sheboygan, Wis.

[*] Notice: This patent is subject to a terminal dis-

claimer.

[**] Term: **14 Years**

[21] Appl. No.: **29/113,326**

[22] Filed: Nov. 1, 1999

359/838, 843, 844, 850, 868, 871, 872, 874, 876, 877, 881, 841; 248/475.1, 480,

481, 479, 487, 494, 483

[56] References Cited

U.S. PATENT DOCUMENTS

D. 372,450	8/1996	Santo	•••••	D12/187
D. 394,833	6/1998	Muth		D12/187
D. 409,540	5/1999	Muth	•••••	D12/187

Primary Examiner—Ralf Seifert

Attorney, Agent, or Firm—Wells, St. John, Roberts, Gregory & Matkin, P.S.

[57] CLAIM

The ornamental design for a combined rearview mirror and nine pixel signalling indicator, as shown and described.

[11] Patent Number: Des. 428,373

[45] Date of Patent: ** *Jul. 18, 2000

DESCRIPTION

FIG. 1 is a perspective view of a combined rearview mirror and nine pixel signalling indicator showing our new design, and with the signalling indicator energized, and with the broken line showing for illustrative purposes only and forming no part of the claim design;

FIG. 2 is a second perspective view of the combined rearview mirror and nine pixel signalling indicator showing our new design and with the signalling indicator deenergized, and with the broken line showing for illustrative purposes only and forming no part of the claim design;

FIG. 3 is a perspective view from a second direction of the combined rearview mirror and nine pixel signalling indicator showing our new design, and with the signalling indicator energized, and with the broken line showing for illustrative purposes only and forming no part of the claim design;

FIG. 4 is a perspective view taken from the same position as FIG. 3 of the combined rearview mirror and nine pixel signalling indicator showing our new design, and with the signalling indicator deenergized, and with the broken line showing for illustrative purposes only, and forming no part of the claim design;

FIG. 5 is a front elevation view of the combined rearview mirror and nine pixel signalling indicator of FIG. 1, and showing the signalling indicator energized;

FIG. 6 is a front elevation view of the combined rearview mirror and nine pixel signalling indicator of FIG. 1, and showing the signalling indicator deenergized;

FIG. 7 is a rear elevation view of the combined rearview mirror and nine pixel signalling indicator of FIG. 1;

FIG. 8 is a top plan view of the combined rearview mirror and nine pixel signalling indicator of FIG. 1;

FIG. 9 is a bottom plan view of the combined rearview mirror and nine pixel signalling indicator of FIG. 1;

FIG. 10 is a side elevation view of the combined rearview mirror and nine pixel signalling indicator of FIG. 1; and,

FIG. 11 is a side elevation view of the combined rearview mirror and nine pixel signalling indicator of FIG. 1, and which is taken from a position opposite to that shown in FIG. 10.

1 Claim, 8 Drawing Sheets























