



US00D429012S

United States Patent [19]
Petruzzi

[11] **Patent Number: Des. 429,012**

[45] **Date of Patent: ** Aug. 1, 2000**

[54] **REPLICA BOTTLE LIGHT**

[76] Inventor: **Thomas G. Petruzzi**, 5118 Belleville Ave., Orlando, Fla. 32812

[**] Term: **14 Years**

[21] Appl. No.: **29/105,254**

[22] Filed: **May 18, 1999**

Related U.S. Application Data

[62] Division of application No. 29/096,971, Nov. 24, 1998, Pat. No. Des. 419,705.

[51] **LOC (7) Cl.** **26-02**

[52] **U.S. Cl.** **D26/38**

[58] **Field of Search** D26/37-50; D9/516, D9/523, 569; 362/161, 311, 392, 194-208, 804, 806

References Cited

U.S. PATENT DOCUMENTS

D. 390,983	2/1998	Petruzzi	D26/38
D. 400,276	10/1998	Petruzzi	D26/38
D. 412,588	8/1999	Petruzzi	D26/38
D. 417,020	11/1999	Petruzzi	D26/38

Primary Examiner—Marcus A. Jackson
Attorney, Agent, or Firm—Allen,Dyer,Doppelt, Milbrath & Gilchrist,PA

CLAIM

The ornamental design for a replica bottle light, as shown and described.

DESCRIPTION

FIG. 1 is a top, left perspective view of a replica bottle light showing my new design;

FIG. 2 is a right side view thereof, the left side being a mirror image;

FIG. 3 is a top plan view thereof;

FIG. 4 is a bottom plan view thereof;

FIGS. 5, 6 and 7 are top, left perspective views of alternate embodiments of FIG. 1, the only difference being a key chain connector;

FIG. 8 is a top, left perspective view of a second embodiment of FIG. 1;

FIG. 9 is a left side view thereof;

FIG. 10 is a front view thereof;

FIG. 11 is a top plan view thereof;

FIG. 12 is a bottom plan view thereof;

FIGS. 13, 14 and 15 are top, left perspective views of alternate embodiments of FIG. 8, the only difference being a key chain connector;

FIG. 16 is a top, left perspective view of a third embodiment of FIG. 1;

FIG. 17 is a right side view thereof, the left side being a mirror image;

FIG. 18 is a top plan view thereof;

FIG. 19 is a bottom plan view thereof;

FIGS. 20, 21, and 22 are top, left perspective views of alternate embodiments of FIG. 16, the only difference being a key chain connector;

FIG. 23 is a top, left perspective view of a fourth embodiment of FIG. 1;

FIG. 24 is a right side view thereof, the left side being a mirror image;


FIG. 25 is a top plan view thereof;

FIG. 26 is a bottom plan view thereof; and,

FIGS. 27, 28, and 29 are top, left perspective views of alternate embodiments of FIG. 23, the only difference being a key chain connector.

The broken line showings herein presented are for illustrative purposes only and do not form a part of the claimed invention.

1 Claim, 5 Drawing Sheets






FIG. 1




FIG. 3




FIG. 4




FIG. 2




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 11




FIG. 12




FIG. 10




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 18




FIG. 19



FIG. 17




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 25




FIG. 26




FIG. 24




FIG. 27




FIG. 28




FIG. 29