



US00D429480S

United States Patent [19] Bonko

[11] Patent Number: **Des. 429,480**

[45] Date of Patent: **** Aug. 15, 2000**

[54] **TIRE**

[75] Inventor: **Mark Leonard Bonko**, Uniontown, Ohio

[73] Assignee: **The Goodyear Tire & Rubber Company**, Akron, Ohio

[**] Term: **14 Years**

[21] Appl. No.: **29/110,415**

[22] Filed: **Sep. 3, 1999**

[51] **LOC (7) Cl.** **12-15**

[52] **U.S. Cl.** **D12/152**

[58] **Field of Search** D12/134-152;
152/209.1, 209.8, 209.9, 209.11, 209.13,
209.16, 209.28, 900, 901

3,865,169 2/1975 Tsuruta 152/209.1
5,044,413 9/1991 Noma et al. 152/209.16
5,188,683 2/1993 Bonko 152/209.16

OTHER PUBLICATIONS

General Super Sand Flotation Tire, 1998 Tread Design Guide, p. 174 4/4.
Bilt-Mor Front Wheel Maxi-Trac Front Tractor Tire, 1998 Tread Design Guide, p. 186 1/4.
Ceat Implement Farm Implement Tire, 1998 Tread Design Guide, p. 186 2/5.
Delta Front Wheel Tire, 1998 Tread Design Guide, p. 188 2/5.

Primary Examiner—Robert M. Spear
Attorney, Agent, or Firm—David L King

[57] CLAIM

The ornamental design for a tire, as shown and described.

DESCRIPTION


FIG. 1 is a perspective view of a tire, it being understood that the tread pattern of the tire repeats uniformly throughout the circumference of the tread;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a side elevational view thereof, the opposite side elevational view being a mirror image thereof; and,
FIG. 4 is a cross-sectional view thereof.

1 Claim, 4 Drawing Sheets

[56] References Cited

U.S. PATENT DOCUMENTS

| | | | | |
|------------|---------|-----------------|-------|-----------|
| D. 106,000 | 9/1937 | Prayle | | D12/152 |
| D. 129,564 | 9/1941 | Rideout | | D12/152 |
| D. 202,161 | 8/1965 | Loughley et al. | | D12/152 |
| D. 276,513 | 11/1984 | Honsa | | D12/135 |
| D. 355,235 | 2/1995 | Homma | | D12/135 |
| D. 398,692 | 9/1998 | Wilson et al. | | D12/152 |
| D. 413,556 | 9/1999 | Krupa et al. | | D12/141 |
| 1,458,629 | 6/1923 | Raymond | | D12/152 X |
| 3,606,921 | 9/1971 | Grawey | | D12/134 X |






FIG-1




FIG-2




FIG-3




FIG-4