



US00D432405S

**United States Patent** [19]  
**Lodi**

[11] **Patent Number: Des. 432,405**

[45] **Date of Patent: \*\* Oct. 24, 2000**

[54] **WIRE ROUTING DEVICE WITH A KEYSLOT LOCKING BASE**

3,702,612 11/1972 Schlesinger .  
5,219,134 6/1993 Morita et al. .

[75] Inventor: **Frank Lodi, Niles, Ill.**

*Primary Examiner*—B. J. Bullock  
*Attorney, Agent, or Firm*—Martin Faier; Faier & Faier, P.C.

[73] Assignee: **Richco, Inc., Chicago, Ill.**

[\*\*] Term: **14 Years**

[57] **CLAIM**

The ornamental design for a wire routing device with a keyslot locking base, as shown and described.

[21] Appl. No.: **29/107,966**

**DESCRIPTION**

[22] Filed: **Jul. 16, 1999**

[51] **LOC (7) Cl. .... 08-08**

FIG. 1 is a perspective view of a device embodying the invention.

[52] **U.S. Cl. .... D8/395; D8/396**

FIG. 2 is a front elevational view of a device embodying the invention.

[58] **Field of Search .... D8/356, 395, 396; D13/154, 199; 248/68.1, 73, 74.2, 220.41, 220.12, 220.11, 222.41, 316.7; 174/164**

FIG. 3 is a rear elevational view of a device embodying the invention.

[56] **References Cited**

FIG. 4 is a top view of a device embodying the invention.

FIG. 5 is a bottom view of a device embodying the invention; and,

**U.S. PATENT DOCUMENTS**

FIG. 6 is a side view of a device embodying the invention, both the left and right side being substantially identical and mirror images of one another.

|            |        |         |       |         |
|------------|--------|---------|-------|---------|
| D. 302,938 | 8/1989 | Fujioka | ..... | D8/395  |
| D. 424,410 | 5/2000 | Lodi    | ..... | D8/356  |
| D. 428,394 | 7/2000 | Lodi    | ..... | D13/199 |
| 1,764,950  | 6/1930 | Griner  | .     |         |
| 3,688,635  | 9/1972 | Fegen   | .     |         |

**1 Claim, 1 Drawing Sheet**



