



US00D434699S

**United States Patent** [19]  
**Pfeiffer**

[11] **Patent Number: Des. 434,699**

[45] **Date of Patent: \*\* Dec. 5, 2000**

[54] **SURFACE CONFIGURATION OF A VEHICLE BODY AND/OR TOY**

[75] Inventor: **Peter Pfeiffer**, Boeblingen, Germany

[73] Assignee: **DaimlerChrysler AG**, Stuttgart, Germany

[\*\*] Term: **14 Years**

[21] Appl. No.: **29/119,095**

[22] Filed: **Feb. 22, 2000**

[30] **Foreign Application Priority Data**

Aug. 19, 1999 [DE] Germany ..... 4 99 07 613

[51] **LOC (7) Cl.** ..... **12-08**

[52] **U.S. Cl.** ..... **D12/92**

[58] **Field of Search** ..... D12/90-92; 296/185

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

- D. 411,139 6/1999 Lai ..... D12/92
- D. 419,489 1/2000 Sacco et al. .... D12/92
- D. 423,989 5/2000 Lawson ..... D12/92

*Primary Examiner*—Melody N. Brown

*Attorney, Agent, or Firm*—Evenson, McKeown, Edwards & Lenahan, P.L.L.C.

[57] **CLAIM**

The ornamental design for a surface configuration of a vehicle body and/or toy, as shown and described.

**DESCRIPTION**

FIG. 1 is a front view of a first embodiment of a surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 2 is a left, front perspective view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 3 is a right, front perspective view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 4 is a left view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 5 is a right view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 6 is a left, rear perspective view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 7 is a right, rear perspective view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 8 is a rear view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 9 is a top view of the first embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 10 is a front view of a second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 11 is a left, front perspective view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 12 is a right, front perspective view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 13 is a left view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 14 is a right view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 15 is a left, rear perspective view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 16 is a right, rear perspective view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 17 is a rear view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 18 is a top view of the second embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;




FIG. 19 is a front view of a third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 20 is a left, front perspective view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 21 is a right, front perspective view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 22 is a left view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 23 is a right view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 24 is a left, rear perspective view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 25 is a right, rear perspective view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design;

FIG. 26 is a rear view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design; and,

FIG. 27 is a top view of the third embodiment of the surface configuration of a vehicle body and/or toy according to my novel design.

The broken lines included depict environment and are not part of the claimed design.

**1 Claim, 18 Drawing Sheets**




FIG. 1




FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10




FIG. 11




FIG. 12




FIG. 13






FIG. 14








FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21






FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27