

US00D435652S

Date of Patent: ** Dec. 26, 2000

Patent Number:

Des. 435,652

United States Patent [19]

14 Years

Mar. 30, 1999

Appl. No.: 29/102,713

Nazarifar et al.

Term:

Filed:

[51]

[52]

[58]

SHIELDED FEMALE CONNECTOR Primary Examiner—James Gandy Assistant Examiner—Reid Hecker

Inventors: Nader Nazarifar, Laguna Niguel;

Attorney, Agent, or Firm—Jeffrey S. Schira Richard A. Rossback, Irvine; Gary P.

[11]

[45]

Sorensen, Lake Forest, all of Calif. [57] CLAIM

567, 568, 571; 606/107

The ornamental design for a shielded female connector, as shown and described.

DESCRIPTION

FIG. 1 is an upper, left, rear perspective view of a first embodiment of the shielded female connector of the present invention.

FIG. 2 is an upper, left, front perspective view of a first embodiment of the shielded female connector of the present invention.

FIG. 3 is an upper plan view of a first embodiment of the shielded female connector of the present invention.

FIG. 4 is a front elevational view of a first embodiment of the shielded female connector of the present invention.

FIG. 5 is a left elevational view of a first embodiment of the shielded female connector of the present invention.

FIG. 6 is a rear elevational view of a first embodiment of the shielded female connector of the present invention.

FIG. 7 is an upper, left, rear perspective view of a second embodiment of the shielded female connector of the present invention.

FIG. 8 is an upper, right, front perspective view of a second embodiment of the shielded female connector of the present invention.

FIG. 9 is an upper plan view of a second embodimen of the shielded female connector of the present invention.

FIG. 10 is a front elevational view of a second embodiment of the shielded female connector of the present invention.

FIG. 11 is a left elevational view of a second embodimen of the shielded female connector of the present invention; and, FIG. 12 is a rear elevational view of a second embodiment of the shielded female connector of the present invention.

The connector of the present invention is used as a fluid connector during microsurgery, particularly ophthalmic surgery, to connect irrigation and aspiration tubings between a surgical handpiece and a control console.

[56] References Cited

U.S. PATENT DOCUMENTS

U.S. Cl. D24/129; D23/262

D24/130; D23/259, 262; 285/40, 390; 604/403,

905, 530, 533, 535, 19, 22, 27, 35; 222/566,

221,864	11/1879	Robbins .
D. 302,729	8/1989	Stephens et al
D. 303,291	9/1989	Magrath
D. 327,318	6/1992	Dudar et al
D. 363,542	10/1995	Parris et al
D. 395,502	6/1998	Deily et al
591,136	10/1897	Lucas .
696,059	3/1902	Line.
714,476	11/1902	Grubbs .
761,643	6/1904	Backman.

(List continued on next page.)

FOREIGN PATENT DOCUMENTS


1218237	6/1966	Germany.
67082	11/1943	Norway .
587987	5/1947	United Kingdom.
2198963	6/1988	United Kingdom.

OTHER PUBLICATIONS

Qosina 1999 Components, pp. cover, 36, 54, 55.


Borla 1999 Plastic and Rubber Components for Medical Use, pp. 3, 32–35, 44–45m 47m 49, 50, 60.


1 Claim, 8 Drawing Sheets



Des. 435,652 Page 2

	U.S. PA	TENT DOCUMENTS	4,983,160 5,176,415		Steppe et al 604/22
	-	Toole et al Johnson et al	, ,	-	Doherty 604/905
936,566	10/1909	Rosendahl .	, ,		Dalton
, ,	4/1985	Oreopoulous et al	5,540,707	7/1996	Ressemann et al 604/22
, ,		Lumsden et al Kawano et al	5,620,427 5,951,519	-	Werschmidt et al 604/535 Utterberg .
4,808,154	2/1989	Freeman 604/22	6,042,586	3/2000	Kawano et al 606/107








FIG. 3








FIG. 4












FIG. 9

