



US00D436334S

(12) **United States Design Patent**
Takizawa

(10) **Patent No.:** **US D436,334 S**

(45) **Date of Patent:** **** Jan. 16, 2001**

(54) **BRAKE SHOE SUPPORT BODY**

(75) Inventor: **Shin'ichi Takizawa, Sakai (JP)**

(73) Assignee: **Shimano Inc., Osaka (JP)**

(**) Term: **14 Years**

(21) Appl. No.: **29/120,417**

(22) Filed: **Mar. 21, 2000**

Related U.S. Application Data

(62) Division of application No. 29/077,793, filed on Oct. 14, 1997.

(51) **LOC (7) Cl.** **12-16**

(52) **U.S. Cl.** **D12/180**

(58) **Field of Search** D12/180; 188/24.11-24.14,
188/24.22, 73.1

(56) **References Cited**

U.S. PATENT DOCUMENTS

D. 281,874	12/1985	King	D12/180
D. 295,847	5/1988	Everett	D12/180
D. 379,344	5/1997	Everett	D10/180
D. 384,018	9/1997	Nishimura	D12/179
D. 397,071	* 8/1998	Hsueh	D12/180
D. 426,181	* 6/2000	Everett	D12/180
3,305,048	2/1967	Brilando	188/24
3,840,093	10/1974	Hamayasu	188/24
5,655,629	8/1997	Takizawa et al.	188/24.12

* cited by examiner

Primary Examiner—Melody N. Brown

(74) *Attorney, Agent, or Firm*—Shinju Global IP Counselors, LLP

(57) **CLAIM**

The ornamental design for a brake shoe support body for a bicycle brake mechanism, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the brake shoe support body showing my new design in accordance with one embodi-

ment of the present invention, with a brake pad and an attachment screw shown in broken lines;

FIG. 2 is a bottom view of the brake shoe support body depicted in FIG. 1, showing my new design, with the attachment screw removed for clarity and the brake pad shown in broken lines.

FIG. 3 is a side view of the brake shoe support body depicted in FIG. 1, showing my new design, with the attachment screw removed for clarity and the brake pad shown in broken lines;

FIG. 4 is a top view of the brake shoe support body depicted in FIG. 1, showing my new design, with the attachment screw removed for clarity and the brake pad shown in broken lines;

FIG. 5 is an end view of the brake shoe support body depicted in FIG. 1, showing my new design, with the attachment screw removed for clarity and the brake pad shown in broken lines;

FIG. 6 is a perspective view of the brake shoe support body showing my new design in accordance with a second embodiment of the present invention, with a brake pad and an attachment screw shown in broken lines;

FIG. 7 is a bottom view of the brake shoe support body depicted in FIG. 6, showing my new design, with the attachment screw and the brake pad removed for clarity;

FIG. 8 is a side view of the brake shoe support body depicted in FIG. 6, showing my new design, with the attachment screw and the brake pad removed for clarity;

FIG. 9 is a top view of the brake shoe support body depicted in FIG. 6, showing my new design, with the attachment screw and the brake pad removed for clarity; and,

FIG. 10 is an end view of the brake shoe support body depicted in FIG. 6, showing my new design, with the attachment screw and the brake pad removed for clarity.

A view showing the portion of the brake shoe support body where the brake pad is attached is not provided because there is no ornamentation on that surface of the brake shoe support body. A further end view of each embodiment of the brake shoe support body is not provided because the end views are generally mirror images of one another.

The broken line showing of environment features shown throughout the drawings are for illustrative purposes only and forms no part of the claimed design.

1 Claim, 4 Drawing Sheets




FIG. 1




FIG. 2



FIG. 3




FIG. 4



FIG. 5



FIG. 6




FIG. 7



FIG. 8




FIG. 9




FIG. 10

