



US00D437844S

(12) **United States Design Patent**
Sayers et al.

(10) **Patent No.:** **US D437,844 S**

(45) **Date of Patent:** **** Feb. 20, 2001**

(54) **TRANSCEIVER BASE**

(75) **Inventors:** **Ian Leslie Sayers**, Redwood City;
Michael Allan Neiman, Santa Rosa;
Richard William Benner, Fremont, all
of CA (US)

(73) **Assignee:** **Cisco Systems, Inc.**, San Jose, CA (US)

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/112,096**

(22) **Filed:** **Oct. 8, 1999**

(51) **LOC (7) Cl.** **14-03**

(52) **U.S. Cl.** **D14/240; D14/358; D14/137**

(58) **Field of Search** D14/137, 140,
D14/142, 358, 155, 159, 240, 242, 241,
308, 310, 311, 312; 379/419, 420, 428,
440, 399, 412; 455/550-575, 90; D13/184,
133, 152, 123, 179; 361/704, 722, 726,
801, 688

(56) **References Cited**

U.S. PATENT DOCUMENTS

D. 287,718	*	1/1987	Moeller	D13/123
D. 292,914	*	11/1987	Moeller	D13/123
D. 336,074	*	6/1993	Friend et al.	D13/184
D. 379,088	*	5/1997	Hopper	D13/152
D. 395,897	*	7/1998	Honma et al.	D14/240
D. 398,295	*	9/1998	Chang	D14/114
D. 416,873	*	11/1999	Korsunsky et al.	D13/184
3,421,578	*	1/1969	Marton	165/186
4,541,004	*	9/1985	Moore	257/706

5,065,278	*	11/1991	Schultz	361/688
5,150,278	*	9/1992	Lynes et al.	361/690
5,276,585	*	1/1994	Smithers	361/704
5,369,301	*	11/1994	Hayashi et al.	257/722
5,396,402	*	3/1995	Perugini et al.	361/704
5,421,406	*	6/1995	Furusawa et al.	165/185
5,435,384	*	7/1995	Wu	165/185
5,594,624	*	1/1997	Clemens et al.	361/704
5,600,540	*	2/1997	Blomquist	361/704
5,771,468	*	6/1998	Stein	455/561
6,008,750	*	12/1999	Cottle et al.	342/42
6,065,530	*	5/2000	Austin et al.	165/80.3

* cited by examiner

Primary Examiner—Jeffrey Asch

(74) *Attorney, Agent, or Firm*—Hamilton, Brook, Smith & Reynolds, P.C.

(57) **CLAIM**

The ornamental design for transceiver base, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of the transceiver base showing my the new design.

FIG. 2 is a back perspective view of the transceiver base.

FIG. 3 is a front view of the transceiver base.

FIG. 4 is a back view of the transceiver base.



FIG. 5 is a top plan view of the transceiver base.

FIG. 6 is a left side view of the transceiver base.

FIG. 7 is a right side view of the transceiver base; and,

FIG. 8 is a bottom plan view of the transceiver base.

1 Claim, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 8




FIG. 6




FIG. 7

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : Des 437,844 S

Page 1 of 1

DATED : February 20, 2001

INVENTOR(S) : Ian Leslie Sayers, Michael Allan Neiman and Richard William Benner

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Description,

Line 2, delete "my".

Signed and Sealed this

Sixth Day of November, 2001

Attest:

Nicholas P. Godici

Attesting Officer

NICHOLAS P. GODICI
Acting Director of the United States Patent and Trademark Office