



US00D438509S

(12) **United States Design Patent**
Umeda et al.

(10) **Patent No.:** **US D438,509 S**
(45) **Date of Patent:** **** Mar. 6, 2001**

(54) **STATOR OF A VEHICLE ALTERNATOR**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Atsushi Umeda**, Okazaki; **Tsutomu Shiga**, Nukata-gun; **Shin Kusase**, Obu, all of (JP)

92/06527 4/1992 (WO) .

* cited by examiner

(73) Assignee: **Denso Corporation**, Kariya (JP)

Primary Examiner—Joel Sincavage

(**) Term: **14 Years**

(74) *Attorney, Agent, or Firm*—Pillsbury Madison & Sutro LLP

(21) Appl. No.: **29/097,915**

(22) Filed: **Dec. 16, 1998**

(30) **Foreign Application Priority Data**

Jun. 16, 1998 (JP) 10-17376

(51) **LOC (7) Cl.** **13-02**

(52) **U.S. Cl.** **D13/122**

(58) **Field of Search** D13/122; 310/68 B, 310/263, 156

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,710,657	*	12/1987	Ocken et al.	310/62
4,741,098	*	5/1988	Barrera	29/736
4,890,050	*	12/1989	Mackevich	310/68 C X
5,327,037	*	7/1994	Rasmussen	310/232
5,429,687	*	7/1995	Goffart	148/120
5,504,382	*	4/1996	Douglass et al.	310/156
5,640,062	*	6/1997	Yockey	310/68 B X
5,729,886	*	3/1998	Olson et al.	29/598

(57) **CLAIM**

The ornamental design for a stator for a vehicle alternator, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a stator of a vehicle alternator according to a first embodiment;
 FIG. 2 is a plan view thereof;
 FIG. 3 is a rear view thereof;
 FIG. 4 is a bottom view thereof;
 FIG. 5 is a right side view thereof;
 FIG. 6 is a left side view thereof;
 FIG. 7 is a perspective view thereof;
 FIG. 8 is a front view of a main part of a stator according to a second embodiment; and,
 FIG. 9 is a perspective view of a main part of the stator illustrated in FIG. 8.

The broken line showing is included for the purpose of illustrating the stator and forms no part of the claimed design.

The product related to this design is a stator of an alternator for a vehicle composed of a stator core and coils. As an embodiment, a rotor is rotatably supported in the inner periphery of the product fixed to a housing of the alternator.

1 Claim, 5 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

