



US00D440401S

(12) **United States Design Patent**
Pauser et al.

(10) **Patent No.: US D440,401 S**
(45) **Date of Patent: ** Apr. 17, 2001**

(54) **CONTAINER**

(75) Inventors: **Herbert Pauser**, Darmstadt; **Peter Maier**, Neidlingen, both of (DE)

(73) Assignee: **FESTO Tooltechnic GmbH & Co.**, Esslingen (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/112,260**

(22) Filed: **Oct. 13, 1999**

(30) **Foreign Application Priority Data**

Jun. 7, 1999 (XH) DM/048 172

(51) **LOC (7) Cl.** **03-01**

(52) **U.S. Cl.** **D3/276; D3/294; D3/273**

(58) **Field of Search** **D3/273, 276, 279, D3/281, 282, 294, 905; 206/349, 373, 508, 510; 190/18 A, 100, 110, 111, 112**

(56) **References Cited**

U.S. PATENT DOCUMENTS

D. 315,870	*	4/1991	Perdue, Jr. et al.	D9/420
D. 327,646	*	7/1992	Hardigg et al.	D9/424
D. 331,836	*	12/1992	Newby, Sr.	D3/905
D. 364,426	*	11/1995	Bucaccio	D3/273
D. 394,280	*	5/1998	Cheris et al.	D3/273
D. 401,763	*	12/1998	Wolff	D3/302
D. 414,038	*	9/1999	Van Rhienen	D3/273
4,351,448	*	9/1982	Ingersoll et al.	206/508

* cited by examiner

Primary Examiner—Philip S. Hyder

(74) *Attorney, Agent, or Firm*—Flynn, Thiel, Boutell & Tanis, P.C.

(57) **CLAIM**

The ornamental design for a container, as shown and described herein.

DESCRIPTION

FIG. 1 is a front, top, right isometric view of a container embodying the new design, the lid for the container being shown in the open position, the latch being shown in the stowed position and the handle being shown in a rear and retracted stowed position;

FIG. 2 is a front view of the container showing the lid in the closed position, the latch in the stowed position and the handle being shown in a front and retracted stowed position;

FIG. 3 is a rear view thereof when the handle is in the front and retracted stowed position;

FIG. 4 is a left side view of FIG. 2;

FIG. 5 is a right side view of FIG. 2;

FIG. 6 is a top view of FIG. 2;

FIG. 7 is a bottom view of FIG. 2;

FIG. 8 is a rear, top, right isometric view thereof, the lid being in the closed position, the latch being in the stowed position and the handle being shown in the front and retracted stowed position;


FIG. 9 is a front, top, right isometric view thereof, the lid being in the closed position, the latch being in the stowed position and the handle being shown in the front and retracted position;

FIG. 10 is a right side view similar to FIG. 5, except that the handle is in the deployed and extended position, and the latch is in the stowed position;

FIG. 11 is an isometric view similar to FIG. 9, except that the handle is in the deployed and extended position, and the latch is in the stowed position; and,

FIG. 12 is a front, top, right isometric view similar to FIG. 9, except that the handle is in an extended position.

1 Claim, 12 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12