



US00D442104S

(12) **United States Design Patent**
Costa et al.(10) Patent No.: **US D442,104 S**
(45) Date of Patent: ** May 15, 2001(54) **COMBINED HORN AND STROBE ALARM SIGNAL**(75) Inventors: **Hilario S. Costa**, Sarasota; **Robert Right**, Holmes Beach; **Bruno Drudi**, Port Charlotte, all of FL (US)(73) Assignee: **General Signal Corp.**, Muskegon, MI (US)(**) Term: **14 Years**(21) Appl. No.: **29/122,299**(22) Filed: **Apr. 25, 2000**(51) LOC (7) Cl. **10-05**(52) U.S. Cl. **D10/106**(58) Field of Search D10/104, 106,
D10/116, 121; 340/540, 545, 550, 565,
571, 572, 573(56) **References Cited**

U.S. PATENT DOCUMENTS

D. 339,079 * 9/1993 Behlke D10/106
D. 416,260 11/1999 Harvey et al. D14/215
5,914,665 6/1999 Thorp et al. 340/691.1

* cited by examiner

Primary Examiner—Marcus A. Jackson

(74) Attorney, Agent, or Firm—Pepper Hamilton, LLP

(57) **CLAIM**

The ornamental design for a combined horn and strobe alarm signal, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the combined horn and strobe alarm signal showing first and second embodiments of our new design;

FIG. 2 is a front view of the first and second embodiments of the combined horn and strobe alarm signal of FIG. 1;
FIG. 3 is a rear view of the first embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 4 is a top view of the first embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 5 is a bottom view of the first embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 6 is a right side view of the first embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 7 is a left side view of the first embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 8 is a rear view of the second embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 9 is a right side view of the second embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 10 is a left side view of the second embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 11 is a top view of the second embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 12 is a bottom view of the second embodiment of the combined horn and strobe alarm signal of FIG. 1;
FIG. 13 is a perspective view of a third embodiment of the combined horn and strobe alarm signal of our new design;
FIG. 14 is a front view of the third embodiment of the combined horn and strobe alarm signal of FIG. 13;
FIG. 15 is a side view of the third embodiment of the combined horn and strobe alarm signal of FIG. 13, the other side view being a mirror image thereof;
FIG. 16 is a top view of the third embodiment of the combined horn and strobe alarm signal of FIG. 13; and,
FIG. 17 is a bottom view of the third embodiment of the combined horn and strobe alarm signal of FIG. 13.


1 Claim, 7 Drawing Sheets

FIG. 1











FIG. 2



**FIG. 3****FIG. 4****FIG. 5**

**FIG. 6****FIG. 7****FIG. 8**




FIG. 9

FIG. 10




FIG. 11




FIG. 12




FIG. 13







FIG. 14

FIG. 15**FIG. 16****FIG. 17**