



US00D442282S

(12) **United States Design Patent**
Taylor et al.

(10) **Patent No.:** **US D442,282 S**

(45) **Date of Patent:** **** May 15, 2001**

(54) **PIN CYLINDER**

6,152,925 * 11/2000 Marsh et al. 606/54

(75) Inventors: **Harold S. Taylor; J. Charles Taylor,**
both of Memphis, TN (US)

(73) Assignee: **Smith & Nephew, Inc.,** Memphis, TX
(US)

(**) Term: **14 Years**

(21) Appl. No.: **29/117,929**

(22) Filed: **Feb. 1, 2000**

(51) **LOC (7) Cl.** **24-02**

(52) **U.S. Cl.** **D24/143**

(58) **Field of Search** D24/143, 155,
D24/140, 145; 606/155, 151, 53, 54, 61,
68, 60, 58, 59, 56, 73-79, 69, 72

(56) **References Cited**

U.S. PATENT DOCUMENTS

D. 377,095	*	12/1996	Michelson	D24/143
4,244,360	*	1/1981	Dohogne	606/59
4,969,886	*	11/1990	Cziffer et al.	606/59
5,984,928	*	11/1999	Hermann	606/72

OTHER PUBLICATIONS

“The Rancho Mounting Technique for Circular External Fixator”, Stuart A. Green, MD, *Advances in Orthopaedic Surgery*, Nov./Dec. 1992, pp. 191-200.

“Wireless” Smith & Nephew brochure, copyright 1997, Smith & Nephew publication number 7108-0214.

* cited by examiner

Primary Examiner—Antoine Duval Davis

(74) *Attorney, Agent, or Firm*—George K. Stacey

(57) **CLAIM**

The ornamental design for a “pin cylinder”, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the “pin cylinder” showing our new design;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a side elevational view thereof; and,

FIG. 4 is a top view thereof.

1 Claim, 1 Drawing Sheet




Figure 3




Figure 2




Figure 1




Figure 4

