



US00D443219S

(12) **United States Design Patent**  
**Iwanaga**

(10) **Patent No.:** **US D443,219 S**

(45) **Date of Patent:** **\*\* Jun. 5, 2001**

(54) **WATCH DIAL**

(75) **Inventor:** **Kazuo Iwanaga, Tokyo (JP)**

(73) **Assignee:** **Seiko Kabushiki Kaisha, Tokyo (JP)**

(\*\*) **Term:** **14 Years**

(21) **Appl. No.:** **29/111,863**

(22) **Filed:** **Oct. 5, 1999**

(30) **Foreign Application Priority Data**

Apr. 5, 1999 (JP) ..... 11-8822

(51) **LOC (7) Cl.** ..... **10-07**

(52) **U.S. Cl.** ..... **D10/126**

(58) **Field of Search** ..... D10/1-40, 122-132;  
368/10, 276, 277, 285, 316-317, 223, 228,  
229, 232, 280-282

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D. 24,689	*	9/1895	Jacot	.....	D10/126
D. 53,245	*	4/1919	Hull	.....	D10/126
D. 84,240	*	5/1931	Heinmuller	.....	D10/126
D. 145,610	*	9/1946	Banick	.....	D10/124
D. 163,396	*	5/1951	Lerman	.....	D10/126
D. 164,601	*	9/1951	Plepla	.....	D10/126
D. 173,100	*	9/1954	Cahn	.....	D10/40
D. 198,536	*	6/1964	Dold	.....	D10/122
D. 205,596	*	8/1966	Marti et al.	.....	D10/126
D. 209,070	*	10/1967	Hetzel	.....	D10/126
D. 314,341	*	2/1991	Skrundens	.....	D10/1
D. 320,563	*	10/1991	Skrundens	.....	D10/1
D. 362,202	*	9/1995	Dumas	.....	D10/126
D. 362,403	*	9/1995	Dumas	.....	D10/126
D. 366,838	*	2/1996	Cousins	.....	D10/40

D. 375,277	*	11/1996	Dumas	.....	D10/126
D. 377,628	*	1/1997	Svast	.....	D10/126
D. 378,201	*	2/1997	Svast	.....	D10/126
D. 395,410	*	6/1998	Harrison	.....	D10/126
D. 406,782	*	3/1999	Dumas	.....	D10/126
2,949,005	*	8/1960	Brault	.....	368/232

\* cited by examiner

*Primary Examiner*—Jeffrey Asch

(74) *Attorney, Agent, or Firm*—Stroock & Stroock & Lavan LLP

(57) **CLAIM**

The ornamental design for a watch dial, as shown in the drawings.

**DESCRIPTION**

FIG. 1 is a front elevational view of the invention;  
 FIG. 2 is top plan view, the opposite side being a mirror image thereof;  
 FIG. 3 is a rear elevational view thereof;  
 FIG. 4 is a right side elevational view, the opposite side being a mirror image thereof;  
 FIG. 5 is an exploded perspective view thereof; and,  
 FIG. 6 is a bottom perspective view showing only the bottom plate, separated from the top plate for convenience of illustration.

The dot-dash line in FIG. 5 indicates that the top portion has been shown exploded away from the bottom portion and that the two parts line up on center when in non-exploded condition. The two tiny cylindrical protuberances seen in FIGS. 2 and 4 extend downward from the bottom of top plate in the space outward from and beneath the numbers “3” and “15” in the exact positions indicated in FIGS. 3 and 5.

**1 Claim, 1 Drawing Sheet**





FIG. 1




FIG. 5




FIG. 2




FIG. 3




FIG. 4



FIG. 6

