



US00D443219S

(12) **United States Design Patent**  
**Iwanaga**

(10) **Patent No.:** **US D443,219 S**

(45) **Date of Patent:** **\*\* Jun. 5, 2001**

(54) **WATCH DIAL**

(75) **Inventor:** **Kazuo Iwanaga, Tokyo (JP)**

(73) **Assignee:** **Seiko Kabushiki Kaisha, Tokyo (JP)**

(\*\*) **Term:** **14 Years**

(21) **Appl. No.:** **29/111,863**

(22) **Filed:** **Oct. 5, 1999**

(30) **Foreign Application Priority Data**

Apr. 5, 1999 (JP) ..... 11-8822

(51) **LOC (7) Cl.** ..... **10-07**

(52) **U.S. Cl.** ..... **D10/126**

(58) **Field of Search** ..... D10/1-40, 122-132;  
368/10, 276, 277, 285, 316-317, 223, 228,  
229, 232, 280-282

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- D. 24,689 \* 9/1895 Jacot ..... D10/126
- D. 53,245 \* 4/1919 Hull ..... D10/126
- D. 84,240 \* 5/1931 Heinmuller ..... D10/126
- D. 145,610 \* 9/1946 Banick ..... D10/124
- D. 163,396 \* 5/1951 Lerman ..... D10/126
- D. 164,601 \* 9/1951 Plepla ..... D10/126
- D. 173,100 \* 9/1954 Cahn ..... D10/40
- D. 198,536 \* 6/1964 Dold ..... D10/122
- D. 205,596 \* 8/1966 Marti et al. .... D10/126
- D. 209,070 \* 10/1967 Hetzel ..... D10/126
- D. 314,341 \* 2/1991 Skrundens ..... D10/1
- D. 320,563 \* 10/1991 Skrundens ..... D10/1
- D. 362,202 \* 9/1995 Dumas ..... D10/126
- D. 362,403 \* 9/1995 Dumas ..... D10/126
- D. 366,838 \* 2/1996 Cousins ..... D10/40

- D. 375,277 \* 11/1996 Dumas ..... D10/126
- D. 377,628 \* 1/1997 Svast ..... D10/126
- D. 378,201 \* 2/1997 Svast ..... D10/126
- D. 395,410 \* 6/1998 Harrison ..... D10/126
- D. 406,782 \* 3/1999 Dumas ..... D10/126
- 2,949,005 \* 8/1960 Brault ..... 368/232

\* cited by examiner

*Primary Examiner*—Jeffrey Asch

(74) *Attorney, Agent, or Firm*—Stroock & Stroock & Lavan LLP

(57) **CLAIM**

The ornamental design for a watch dial, as shown in the drawings.

**DESCRIPTION**

FIG. 1 is a front elevational view of the invention; FIG. 2 is top plan view, the opposite side being a mirror image thereof; FIG. 3 is a rear elevational view thereof; FIG. 4 is a right side elevational view, the opposite side being a mirror image thereof; FIG. 5 is an exploded perspective view thereof; and, FIG. 6 is a bottom perspective view showing only the bottom plate, separated from the top plate for convenience of illustration.

The dot-dash line in FIG. 5 indicates that the top portion has been shown exploded away from the bottom portion and that the two parts line up on center when in non-exploded condition. The two tiny cylindrical protuberances seen in FIGS. 2 and 4 extend downward from the bottom of top plate in the space outward from and beneath the numbers “3” and “15” in the exact positions indicated in FIGS. 3 and 5.

**1 Claim, 1 Drawing Sheet**





FIG. 1




FIG. 5




FIG. 2



FIG. 3




FIG. 4



FIG. 6

