



US00D447095B1

(12) **United States Design Patent** (10) **Patent No.:** **US D447,095 S**
Brusberg (45) **Date of Patent:** **** Aug. 28, 2001**

(54) **BICYCLE STAND**

(76) Inventor: **Bernd Brusberg**, Holzstrasse 33, 65197 Wiesbaden (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/109,798**

(22) Filed: **Aug. 23, 1999**

(30) **Foreign Application Priority Data**

Feb. 23, 1999 (DE) 499 01 824
Feb. 24, 1999 (DE) 499 01 919
Jun. 16, 1999 (DE) 499 05 677

(51) **LOC (7) Cl.** **12-11**

(52) **U.S. Cl.** **D12/120**

(58) **Field of Search** D12/215, 111;
D6/450, 462; 211/5, 17-22, 181.1; 280/293,
281.1; 248/153, 175, 176.1, 908, 915

(56) **References Cited**

U.S. PATENT DOCUMENTS

D. 99,302 * 4/1936 Peace D12/111
D. 100,202 * 6/1936 Clements D12/111
D. 150,765 * 8/1948 Harman et al. D12/111
D. 234,587 * 3/1975 Harris et al. D12/115
D. 302,258 * 7/1989 Kalisch et al. D12/115
D. 369,576 * 5/1996 Johnson et al. D12/115

* cited by examiner

Primary Examiner—Alan P. Douglas

Assistant Examiner—Linda Brooks

(74) *Attorney, Agent, or Firm*—Paul & Paul

(57) **CLAIM**

The ornamental design for a bicycle stand, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view illustrating the design of a bicycle stand in accordance with this invention;

FIG. 2 is a side elevation view of the bicycle stand shown in FIG. 1;

FIG. 3 is a top perspective view of the bicycle stand shown in FIG. 1;

FIG. 4 is a front perspective view of an alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 5 is a top perspective view of the bicycle stand shown in FIG. 4;

FIG. 6 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 7 is a top perspective view of the bicycle stand shown in FIG. 6;

FIG. 8 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 9 is a top perspective view of the bicycle stand shown in FIG. 8;

FIG. 10 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 11 is a top perspective view of the bicycle stand shown in FIG. 10;

FIG. 12 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 13 is a top perspective view of the bicycle stand shown in FIG. 12;

FIG. 14 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 15 is a top perspective view of the bicycle stand shown in FIG. 14;

FIG. 16 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 17 is a top perspective view of the bicycle stand shown in FIG. 16;

FIG. 18 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 19 is a top perspective view of the bicycle stand shown in FIG. 18;




FIG. 20 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 21 is a top perspective view of the bicycle stand shown in FIG. 20;

FIG. 22 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 23 is a top perspective view of the bicycle stand shown in FIG. 22;

FIG. 24 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 25 is a top perspective view of the bicycle stand shown in FIG. 24;

FIG. 26 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 27 is a top perspective view of the bicycle stand shown in FIG. 26;

FIG. 28 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 29 is a top perspective view of the bicycle stand shown in FIG. 28;

FIG. 30 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 31 is a top perspective view of the bicycle stand shown in FIG. 30;

FIG. 32 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 33 is a top perspective view of the bicycle stand shown in FIG. 32;

FIG. 34 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention;

FIG. 35 is a top perspective view of the bicycle stand shown in FIG. 34;

FIG. 36 is a front perspective view of another alternative embodiment of the design of a bicycle stand in accordance with this invention; and,

FIG. 37 is a top perspective view of the bicycle stand shown in FIG. 36.

1 Claim, 18 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20



FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26



FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37