



US00D449024B1

(12) **United States Design Patent**
Lovell et al.

(10) **Patent No.:** **US D449,024 S**

(45) **Date of Patent:** **** Oct. 9, 2001**

(54) **TIRE TREAD**

(75) Inventors: **Timothy Patrick Lovell**, Peninsula;
Paul Bryson Allen; Basil Sameer
Elkurd, both of Akron, all of OH (US)

(73) Assignee: **The Goodyear Tire & Rubber**
Company, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/124,959**

(22) Filed: **Jun. 14, 2000**

(51) **LOC (7) Cl.** **12-15**

(52) **U.S. Cl.** **D12/147**

(58) **Field of Search** D12/134-152;
152/209.1, 209.9, 209.12, 209.22, 209.25

(56) **References Cited**

U.S. PATENT DOCUMENTS

D. 278,617	4/1985	Kojima et al.	D12/147
D. 287,236	12/1986	Yonekura et al.	D12/140
D. 287,349	12/1986	Yonekura et al.	D12/140
D. 287,708	1/1987	Hayakawa	D12/147
D. 293,664	1/1988	Hayakawa et al.	D12/146
D. 296,315	6/1988	Hayakawa et al.	D12/142
D. 313,212	12/1990	Hamada et al.	D12/147
D. 316,239	4/1991	Tsuda et al.	D12/145
D. 350,320	9/1994	Suzuki	D12/147
D. 369,768	5/1996	Wakamatsu	D12/147
D. 380,183	6/1997	Matsuda et al.	D12/147
D. 384,312	9/1997	Powell et al.	D12/147
D. 386,730	11/1997	Hubbell, Jr.	D12/147
D. 390,515 *	2/1998	Godsey et al.	D12/147
D. 390,519	2/1998	White	D12/147
D. 397,648	9/1998	Allen et al.	D12/147
D. 402,240	12/1998	Hubbell, Jr.	D12/146
D. 403,955 *	1/1999	Williams	D12/146
D. 414,447	9/1999	Weber et al.	D12/143
D. 421,584 *	3/2000	Lovell et al.	D12/147
4,474,223	10/1984	Landers	152/209 R
4,986,324	1/1991	Suzuki et al.	152/209 R

5,125,444	6/1992	Yoshida	152/209 R
5,137,068	8/1992	Loidl et al.	152/209 R
5,293,918	3/1994	Tsuda et al.	152/209 R
5,360,043	11/1994	Croyle et al.	152/209 A
5,361,816	11/1994	Hitzky	152/209 R
5,388,625	2/1995	White	152/209 R
5,580,404	12/1996	Hitzky	152/209 R
5,871,598	2/1999	Tomita	152/209 R

OTHER PUBLICATIONS

Delta Sierradial Tire, Tread Design Guide, Jan. 1999, p. 26. 1/3.*
GT Tire USA GTR 378 Tire, Tread Design Guide, Jan. 1999, p. 37. 4/1.*
Mastercraft A/S IV Tire, Tread Design Guide, Jan. 1999, p. 46. 4/5.*
Roadmaster Roughneck TE Tire, Tread Design Guide, Jan. 1999, p. 114. 3/3.*

* cited by examiner

Primary Examiner—Robert M. Spear
(74) *Attorney, Agent, or Firm*—David E. Wheeler


(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire tread showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a side elevational view thereof, the opposite side elevational view being identical thereto; and,
FIG. 4 is an enlarged fragmentary perspective view.
In the drawings, the broken lines defining the inner bead of the sidewall and the peripheral boundary between the tire tread and the sidewall are for illustrative purposes only and form no part of the claimed design.

1 Claim, 4 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4