



US00D451441B1

(12) **United States Design Patent**
Weber

(10) **Patent No.:** **US D451,441 S**

(45) **Date of Patent:** **** Dec. 4, 2001**

(54) **TIRE TREAD**

5,833,780 11/1998 Kishi et al. 152/209 R
5,871,598 2/1999 Tomita 152/209 R

(75) Inventor: **Michael Joseph Weber**, Mogadore, OH
(US)

OTHER PUBLICATIONS

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

Bridgestone S321 Tire, 1999 Tread Design Guide, Jan. 1999, p. 16. 4/3.*
Goodyear Infitred Tire, 1999 Tread Design Guide, Jan. 1999, p. 35. 2/5.*
Mastyercraft M-R 823 Tire, 1999 Tread Design Guide, Jan. 1999, p. 46. 3/4.*
2000 *Tread Design Guide*, p. 34, Goodyear EAGLE GS-A Tire, (ZR Rated)—B-TL-R-SB-RP-35-40-45-M-RD.

(**) Term: **14 Years**

* cited by examiner

(21) Appl. No.: **29/133,692**

(22) Filed: **Dec. 4, 2000**

(51) **LOC (7) Cl.** **12-15**

(52) **U.S. Cl.** **D12/146**

(58) **Field of Search** D12/134-152;
152/209.1, 209.3, 209.8, 209.9, 209.11,
455, 456, 902, 903, 904

Primary Examiner—Robert M. Spear
(74) *Attorney, Agent, or Firm*—David E. Wheeler

(57) **CLAIM**

(56) **References Cited**

The ornamental design for a tire tread, as shown and described.


U.S. PATENT DOCUMENTS

DESCRIPTION

| | | | |
|--------------|---------|-------------------------|-----------|
| D. 310,804 | 9/1990 | Covert et al. | D12/147 |
| D. 390,820 * | 2/1998 | Guspodin et al. | D12/147 |
| D. 402,946 | 12/1998 | McKisson | D12/147 |
| D. 407,679 | 4/1999 | Weber et al. | D12/147 |
| D. 410,600 * | 6/1999 | Matsuda | D12/146 |
| D. 418,785 * | 1/2000 | Lovell et al. | D12/147 |
| D. 423,422 | 4/2000 | Selover et al. | D12/146 |
| D. 439,870 * | 4/2001 | Lovell et al. | D12/146 |
| 4,649,975 | 3/1987 | Kogure et al. | 152/209 R |
| 5,200,008 | 4/1993 | Enterline et al. | 156/110.1 |
| 5,360,043 | 11/1994 | Croyle et al. | 152/209 A |
| 5,361,814 | 11/1994 | Covert et al. | 152/209 A |
| 5,388,625 | 2/1995 | White | 152/209 R |
| 5,407,005 * | 4/1995 | Consolacion et al. | 152/902 |
| 5,529,101 | 6/1996 | Croyle et al. | 152/209 R |
| 5,804,000 | 9/1998 | Shirai et al. | 152/209 R |
| 5,814,169 | 9/1998 | Yamaguchi et al. | 152/209 R |

FIG. 1 is a perspective view of a tire tread showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;
FIG. 2 is the opposite side perspective view of a tire tread thereof;
FIG. 3 is a front elevational view thereof;
FIG. 4 is a side elevational view thereof;
FIG. 5 is the opposite side elevational view thereof; and,
FIG. 6 is an enlarged fragmentary perspective view.
In the drawings, the broken lines defining the inner bead of the sidewall and the peripheral boundary between the tire tread and the sidewall are for illustrative purposes only and form no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6