

US00D451883B1

## (12) United States Design Patent (10) Patent No.:

US D451,883 S (45) Date of Patent: \*\* Dec. 11, 2001 Reynolds

### REMOTELY SWITCHABLE POWER SUPPLY (54)FOR NETWORK DEVICE RACKS HAVING EIGHT NETWORK SOCKET OPENINGS AND FOUR POWER OUTLET OPENINGS

Charles H. Reynolds, Gilroy, CA (US) Inventor:

Cyber Switching, Inc., Santa Clara, CA (73)

(US)

(\*\*) Term: 14 Years

Appl. No.: 29/104,720

May 11, 1999 Filed:

(52)(58)

> D13/184, 162, 164; 307/150, 151; 361/643, 728

#### (56)**References Cited**

## U.S. PATENT DOCUMENTS

D. 288,092	*	2/1987	Towell et al
D. 288,920	*	3/1987	Oesterheld et al D13/139.8
D. 306,155	*	2/1990	Stahler et al
D. 366,248	*	1/1996	Owens
D. 380,447	*	7/1997	Chen et al
4,731,029	*	3/1988	Lerner et al 439/4
4,840,570	*	6/1989	Mann, Jr. et al 439/74
4,993,970	*	2/1991	Littrell
5,181,858	*	1/1993	Matz et al 438/188
5,199,878	*	4/1993	Dewey et al 439/650
5,245,507	*		Ericksen
5,493,542	*	2/1996	Odelid
•			

(List continued on next page.)

## OTHER PUBLICATIONS

Web Page "http://www.wti.com/power.htm".

Web Page "http://www.dataprobe.com/power1.html".

Primary Examiner—Joel Sincavage

(74) Attorney, Agent, or Firm—Stephen J. LeBlanc; The Law Offices of Jonathan Alan Quine

#### **CLAIM** (57)

The ornamental design for remotely switchable power supply for network device racks having eight network socket openings and four power outlet openings, as shown and described.

## **DESCRIPTION**

This application is related to the following design applications by the same inventor, each of which is incorporated by reference and each of which was filed on the same day as this application: Network Remotely Switchable Power Supply; a/n 29/104,765, filed May 11, 1999; Network Port and Power Outlet Placed on a Switchable Power Supply; a/n 29/104,721 filed May 11, 1999.

The article is a power supply strip that includes power supply receptacles and network connections and that allows a remotely network device to cause the power provided by the power supply receptacle to cycle.

FIG. 1 is a perspective view of a remotely switchable power supply for network device racks having eight network socket openings and four power outlet openings showing my new design;

FIG. 2 is a top plan view thereof;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a right side elevational view, the left side elevational view being a mirror image thereof; and

FIG. 5 is a rear elevational view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a perspective view of a remotely switchable power supply for network device racks having eight network socket openings and four power outlet openings showing flush outlets openings according to an alternative embodiment of my new design;


FIG. 8 is a top plan view of the embodiment shown in FIG. **7**;

FIG. 9 is a right side elevational view of the embodiment shown in FIG. 7, the left side elevational view being a mirror image thereof; and,

FIG. 10 is a bottom plan view of the embodiment shown in FIG. 7.


The broken line showing throughout the drawing figures is included for the purpose of illustrating environmental structure only and forms no part of the claimed design.

## 1 Claim, 4 Drawing Sheets



# US D451,883 S Page 2


U.S. PATENT DOCUMENTS	5,649,839 * 7/1997 <b>Y</b> u
5,531,611 * 7/1996 Reed et al	5,658,166 * 8/1997 Freeman et al
5,538,438 * 7/1996 Orlando	
5,632,648 * 5/1997 Liu	* cited by examiner




F/G. 3.


Dec. 11, 2001







F/G. 5.



F/G. 6.

Dec. 11, 2001

