



US00D452220B1

(12) **United States Design Patent** (10) **Patent No.:** **US D452,220 S**
Robson (45) **Date of Patent:** **** Dec. 18, 2001**

(54) **ARRANGEMENT OF ALUMINUM FOIL COILS FORMING AN INDUCTOR OF A RESONANT FREQUENCY IDENTIFICATION ELEMENT**

(75) Inventor: **David Robson**, Crowborough (GB)

(73) Assignee: **Meto International GmbH**, Hirschhorn (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/136,375**

(22) Filed: **Jan. 31, 2001**

Related U.S. Application Data

(62) Division of application No. 29/103,482, filed on Apr. 15, 1999.

(30) **Foreign Application Priority Data**

Oct. 15, 1998 (DE) 498 10 255

(51) **LOC (7) Cl.** **13-03**

(52) **U.S. Cl.** **D13/182**

(58) **Field of Search** D13/182; 336/12, 336/20, 200, 212; 340/572

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,967,161 * 6/1976 Lichtblau 336/200 X
4,498,076 * 2/1985 Lichtblau 340/572
5,969,590 * 10/1999 Gutierrez 336/200
6,087,922 * 7/2000 Smith 336/200 X
6,114,937 * 9/2000 Burghartz et al. 336/200
6,144,281 * 11/2000 Lorris 336/200
6,147,582 * 11/2000 Goldsmith et al. 336/200

FOREIGN PATENT DOCUMENTS

0755036 * 1/1997 (EP) .

* cited by examiner

Primary Examiner—Brian N. Vinson

(74) *Attorney, Agent, or Firm*—Jones, Tullar & Cooper, P.C.

(57) **CLAIM**

The ornamental design for an arrangement of aluminum foil coils forming an inductor of a resonant frequency identification element, as shown and described.

DESCRIPTION

FIG. 1 is a top view of the arrangement of aluminum foil coils forming an inductor of the resonant frequency identification of the present invention;

FIG. 2 is a bottom view of the arrangement of FIG. 1;

FIG. 3 is a top view of the arrangement of aluminum foil coils mounted on a chip dimensioned differently from the arrangement of FIGS. 1 and 2;

FIG. 4 is a bottom view of the arrangement of FIG. 3;

FIG. 5 is a top view of another arrangement of aluminum foil coils mounted on a chip;

FIG. 6 is a bottom view of the arrangement of FIG. 5;

FIG. 7 is a top view of an arrangement of aluminum foil coils mounted on a chip dimensioned differently from the arrangement of FIGS. 1, 2, 3, 4 and 5;

FIG. 8 is a bottom view of the arrangement of FIG. 5;

FIG. 9 is a top view of another arrangement of aluminum foil coils mounted on a chip;


FIG. 10 is a bottom view of the arrangement of FIG. 9;

FIG. 11 is a top view of an arrangement of aluminum foil coils mounted on a chip dimensioned differently from the arrangement of FIGS. 9 and 10; and,

FIG. 12 is a bottom view of the arrangement of FIG. 11.

The arrangement of coils is of nominal thickness.

1 Claim, 12 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12