



US00D452833B1

(12) **United States Design Patent**
Ito et al.

(10) **Patent No.:** **US D452,833 S**
(45) **Date of Patent:** **** Jan. 8, 2002**

(54) **SEAT OCCUPANT SENSOR**

D438,479 S * 3/2001 Goetz et al. D10/104
D440,169 S * 4/2001 Far D10/104

(75) Inventors: **Koji Ito**, Aichi-ken; **Kazuya Tanaka**, Nagoya; **Hitoshi Takayanagi**, Chiryu, all of (JP)

FOREIGN PATENT DOCUMENTS

WO 99/39168 8/1999

(73) Assignee: **Aisin Seiki Kabushiki Kaisha**, Aichi-ken (JP)

* cited by examiner

(**) Term: **14 Years**

Primary Examiner—Marcus A. Jackson
(74) *Attorney, Agent, or Firm*—Burns, Doane, Swecker & Mathis, L.L.P.

(21) Appl. No.: **29/137,948**

(57) **CLAIM**

(22) Filed: **Mar. 5, 2001**

The ornamental design for a seat occupant sensor, as shown and described.

(30) **Foreign Application Priority Data**

DESCRIPTION

Sep. 5, 2000 (JP) 12-024741

(51) **LOC (7) Cl.** **10-05**

(52) **U.S. Cl.** **D10/104**

(58) **Field of Search** D10/104, 106, D10/116, 121; 340/425.5, 988, 989, 991, 992, 993, 994, 906, 907, 908, 908.1, 909, 910, 911, 915

FIG. 1 is a plan view showing a seat occupant sensor according to the present invention;
FIG. 2 is a rear view of the sensor of FIG. 1, the front view being a mirror image of the rear view;
FIG. 3 is a right side view showing the sensor of FIG. 1, the left side view being a mirror image of the right side view;
FIG. 4 is an enlarged plan view showing the sensor of FIG. 1; and,
FIG. 5 is a perspective view showing the sensor of FIG. 1. The broken lines in FIGS. 1 to 5 are shown for illustrative purposes only and form no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D367,825 S * 3/1996 Webb et al. D10/104
D409,935 S * 5/1999 Speckhart D10/104

1 Claim, 4 Drawing Sheets




Fig. 1




Fig. 2



Fig. 3




Fig.4




Fig.5

