



US00D454951S

(12) **United States Design Patent**
Bon

(10) **Patent No.:** **US D454,951 S**

(45) **Date of Patent:** **** Mar. 26, 2002**

(54) **STEERABLE CATHETER**

(75) **Inventor:** **Edwin Bon**, Canton, GA (US)

(73) **Assignee:** **Visionary Biomedical, Inc.**, Marietta, GA (US)

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/137,775**

(22) **Filed:** **Feb. 27, 2001**

(51) **LOC (7) Cl.** **24-02**

(52) **U.S. Cl.** **D24/112; D24/108; D24/133; D24/138**

(58) **Field of Search** **D24/112, 133, D24/108, 138; 604/95.05, 95.01, 95.04, 250, 34, 35, 30, 19, 45, 902**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,470,876 A	10/1969	Barchilon	
4,353,358 A	10/1982	Emerson	
4,545,369 A	10/1985	Sato	
4,601,284 A	7/1986	Arakawa et al.	
4,651,202 A	3/1987	Arakawa	
4,750,475 A	6/1988	Yoshihashi	
4,884,133 A	11/1989	Kanno et al.	
5,151,096 A	9/1992	Khoury	
5,199,950 A	4/1993	Schmitt et al.	
5,217,454 A	6/1993	Khoury	
5,273,524 A	* 12/1993	Fox et al.	604/21
D343,678 S	1/1994	Snoke et al.	
5,342,299 A	8/1994	Snoke et al.	
5,354,266 A	10/1994	Snoke	
D352,780 S	* 11/1994	Glaeser et al.	D24/133
5,399,164 A	3/1995	Snoke et al.	
5,415,158 A	5/1995	Barthel et al.	
5,437,636 A	8/1995	Snoke et al.	
5,496,269 A	3/1996	Snoke	
5,526,820 A	6/1996	Khoury	
5,531,686 A	7/1996	Lundquist et al.	

5,538,496 A	7/1996	Yabe et al.	
5,542,924 A	8/1996	Snoke et al.	
5,609,573 A	* 3/1997	Sandock	604/22
5,624,397 A	4/1997	Snoke et al.	
5,779,626 A	7/1998	Kondo	
5,846,221 A	12/1998	Snoke et al.	
5,857,996 A	1/1999	Snoke	
5,860,953 A	1/1999	Snoke et al.	
D405,881 S	2/1999	Snoke et al.	
5,868,665 A	2/1999	Biggs	
6,030,360 A	2/2000	Biggs	
6,146,355 A	11/2000	Biggs	
6,213,974 B1	4/2001	Smith et al.	

FOREIGN PATENT DOCUMENTS

EP 0 389 453 A1 9/1990

* cited by examiner

Primary Examiner—Ian Simmons

(74) *Attorney, Agent, or Firm*—Gardner Groff Mehrman & Josephic, P.C.


(57) **CLAIM**

The ornamental design of a steerable catheter, as shown and described.

DESCRIPTION

FIG. 1 is a first perspective view of a steerable catheter according to a preferred form of the present invention; FIG. 2 is a second perspective view of the steerable catheter of FIG. 1; FIG. 3 is a top view of the steerable catheter of FIG. 1; FIG. 4 is a bottom view of the steerable catheter of FIG. 1; FIG. 5 is a front view of the steerable catheter of FIG. 1; FIG. 6 is a rear view of the steerable catheter of FIG. 1; FIG. 7 is a first side view of the steerable catheter of FIG. 1; and, FIG. 8 is a second side view of the steerable catheter of FIG. 1.

1 Claim, 5 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5



Fig. 6




Fig. 1




Fig. 2