



US00D455706S

(12) **United States Design Patent**
Mitchell et al.

(10) **Patent No.:** **US D455,706 S**
(45) **Date of Patent:** **** Apr. 16, 2002**

(54) **CARRIER FOR USE ON A BICYCLE**

(76) Inventors: **William M. Mitchell; Barbara M. Mitchell**, both of 812 Lexington Ave., Charlotte, NC (US) 28203

(**) Term: **14 Years**

(21) Appl. No.: **29/141,109**

(22) Filed: **Apr. 30, 2001**

(51) **LOC (7) Cl.** **12-16**

(52) **U.S. Cl.** **D12/407**

(58) **Field of Search** **D12/407-409; 224/412-439; D3/215-217, 231**

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,362,162 A	*	12/1920	Bradley	224/429
4,720,027 A		1/1988	Board	224/35
4,955,516 A		9/1990	Satterfield	224/35
5,110,020 A		5/1992	Uhl	224/32 R

* cited by examiner

Primary Examiner—Alan P. Douglas

Assistant Examiner—Linda Brooks

(74) *Attorney, Agent, or Firm*—Dougherty & Clements LLP

(57) **CLAIM**

The ornamental design for a carrier for use on a bicycle, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the carrier for use on a bicycle showing the new design folded in half and in use attached to a bicycle;

FIG. 2 is a front side elevational view thereof;

FIG. 3 is a top side elevational view thereof;

FIG. 4 is a bottom side elevational view thereof;

FIG. 5 is a left side elevational view thereof;

FIG. 6 is a right side elevational view thereof;

FIG. 7 is a back side elevational view thereof;

FIG. 8 is a front side view of an alternative embodiment of the present invention having one pocket;

FIG. 9 is a top side elevational view of the alternative embodiment thereof;

FIG. 10 is a bottom side elevational view of the alternative embodiment thereof;

FIG. 11 is a left side elevational view of the alternative embodiment thereof;

FIG. 12 is a front side view of the alternative embodiment thereof;

FIG. 13 is a back side elevational view of the alternative embodiment thereof;

FIG. 14 is a front elevational view of another alternative embodiment of the present invention without a strap and having one pocket;

FIG. 15 is a top side elevational view of the alternative embodiment thereof;

FIG. 16 is a bottom side elevational view of the alternative embodiment thereof;

FIG. 17 is a left side elevational view of the alternative embodiment thereof;

FIG. 18 is a front side view of the alternative embodiment thereof;

FIG. 19 is a back side elevational view of the alternative embodiment thereof;

FIG. 20 is a front view of still another alternative embodiment of the present invention without a strap and having two pockets;

FIG. 21 is a top side elevational view of the alternative embodiment thereof;

FIG. 22 is a bottom side elevational view of the alternative embodiment thereof;

FIG. 23 is a left side elevational view of the alternative embodiment thereof;

FIG. 24 is a front side view of the alternative embodiment thereof;

FIG. 25 is a back side elevational view of the alternative embodiment thereof; and,

FIG. 26 is a perspective view of the present invention in accordance with FIGS. 14 through 25, folded in half and shown in use with a bicycle.

The broken lines shown form no part of the claimed design.

1 Claim, 6 Drawing Sheets




Fig. 1




Fig. 3



Fig. 6




Fig. 2

Fig. 5

Fig. 4




Fig. 7

Fig. 9



Fig. 12




Fig. 8

Fig. 11



Fig. 10




Fig. 13

Fig. 15



Fig. 14




Fig. 18




Fig. 17



Fig. 16




Fig. 19




Fig. 21



Fig. 20




Fig. 24




Fig. 23



Fig. 22



Fig. 25




Fig. 26

