

US00D455706S

(12) **United States Design Patent** (10) **Patent No.:** **US D455,706 S**  
**Mitchell et al.** (45) **Date of Patent:** **\*\* Apr. 16, 2002**

(54) **CARRIER FOR USE ON A BICYCLE**

(76) Inventors: **William M. Mitchell; Barbara M. Mitchell**, both of 812 Lexington Ave., Charlotte, NC (US) 28203

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/141,109**

(22) Filed: **Apr. 30, 2001**

(51) **LOC (7) Cl.** ..... **12-16**

(52) **U.S. Cl.** ..... **D12/407**

(58) **Field of Search** ..... D12/407-409; 224/412-439; D3/215-217, 231

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,362,162 A \* 12/1920 Bradley ..... 224/429  
4,720,027 A 1/1988 Board ..... 224/35  
4,955,516 A 9/1990 Satterfield ..... 224/35  
5,110,020 A 5/1992 Uhl ..... 224/32 R

\* cited by examiner

*Primary Examiner*—Alan P. Douglas

*Assistant Examiner*—Linda Brooks

(74) *Attorney, Agent, or Firm*—Dougherty & Clements LLP

(57) **CLAIM**

The ornamental design for a carrier for use on a bicycle, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of the carrier for use on a bicycle showing the new design folded in half and in use attached to a bicycle;

FIG. 2 is a front side elevational view thereof;

FIG. 3 is a top side elevational view thereof;

FIG. 4 is a bottom side elevational view thereof;

FIG. 5 is a left side elevational view thereof;

FIG. 6 is a right side elevational view thereof;

FIG. 7 is a back side elevational view thereof;

FIG. 8 is a front side view of an alternative embodiment of the present invention having one pocket;

FIG. 9 is a top side elevational view of the alternative embodiment thereof;

FIG. 10 is a bottom side elevational view of the alternative embodiment thereof;

FIG. 11 is a left side elevational view of the alternative embodiment thereof;

FIG. 12 is a front side view of the alternative embodiment thereof;

FIG. 13 is a back side elevational view of the alternative embodiment thereof;

FIG. 14 is a front elevational view of another alternative embodiment of the present invention without a strap and having one pocket;

FIG. 15 is a top side elevational view of the alternative embodiment thereof;

FIG. 16 is a bottom side elevational view of the alternative embodiment thereof;

FIG. 17 is a left side elevational view of the alternative embodiment thereof;

FIG. 18 is a front side view of the alternative embodiment thereof;

FIG. 19 is a back side elevational view of the alternative embodiment thereof;

FIG. 20 is a front view of still another alternative embodiment of the present invention without a strap and having two pockets;

FIG. 21 is a top side elevational view of the alternative embodiment thereof;

FIG. 22 is a bottom side elevational view of the alternative embodiment thereof;

FIG. 23 is a left side elevational view of the alternative embodiment thereof;


FIG. 24 is a front side view of the alternative embodiment thereof;

FIG. 25 is a back side elevational view of the alternative embodiment thereof; and,

FIG. 26 is a perspective view of the present invention in accordance with FIGS. 14 through 25, folded in half and shown in use with a bicycle.

The broken lines shown form no part of the claimed design.

**1 Claim, 6 Drawing Sheets**



*Fig. 1*




Fig.3



Fig.2




Fig.5

Fig.6

Fig.4



Fig.7




Fig.9



Fig.8





Fig.11

Fig.10



Fig.13







Fig. 21



Fig. 20




Fig. 24



Fig. 23





Fig. 22



Fig. 25





*Fig. 26*

