US00D457483S

(12) United States Design Patent

Heinen

(10) Patent No.: US D457,483 S
(45) Date of Patent: ** May 21, 2002

(54) **TIRE TREAD**

(75) Inventor: **Richard Heinen**, Habay-la-Neuve (BE)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/142,239**

(22) Filed: **May 22, 2001**

(51) **LOC (7) Cl.** **12-15**
(52) **U.S. Cl.** **D12/567**; D12/603
(58) **Field of Search** D12/547, 549, D12/550, 551, 553, 555, 556, 566–7, 602–3; 152/209.1, 209.9, 209.13, 209.28

(56) **References Cited**

U.S. PATENT DOCUMENTS

D283,501 S	4/1986	Hitzky	D12/147
4,632,166 A	12/1986	Fontaine et al.	152/209 R
D292,787 S	11/1987	Kadomaru	D12/147
D295,031 S	4/1988	Fontaine et al.	D12/146
D303,363 S	9/1989	Graas	D12/147
D312,063 S	11/1990	Covert et al.	D12/147
D316,067 S	4/1991	Hammond et al.	D12/146
D316,690 S	5/1991	Tagashira	D12/146
D317,145 S	5/1991	Iwamura	D12/146
D328,267 S	7/1992	Constant	D12/146
D328,268 S	7/1992	Constant	D12/146
D329,031 S	9/1992	Lassan	D12/146
D336,068 S	6/1993	Attinello	D12/147
D344,918 S	3/1994	Graas	D12/147
D349,873 S	8/1994	Shibata et al.	D12/141
D354,035 S	1/1995	McKisson	D12/147
D357,218 S	4/1995	Powell	D12/147
D362,220 S	9/1995	Van Emburg	D12/147
D379,441 S	5/1997	Villamzar et al.	D12/141
D379,443 S	5/1997	Arendt et al.	D12/147
D384,607 S	10/1997	Attinello et al.	D12/146
D387,023 S	12/1997	Sato et al.	D12/147
D392,226 S	3/1998	Howald et al.	D12/141
D392,229 S	3/1998	Shirai et al.	D12/147
D400,134 S	10/1998	Sato et al.	D12/147
D403,629 S	1/1999	Guspodin et al.	D12/147
D403,630 S	1/1999	Maxwell et al.	D12/147
D409,954 S	5/1999	Murata	D12/141
D410,601 S	6/1999	Murata et al.	D12/147
D415,984 S	11/1999	Allison et al.	D12/147

OTHER PUBLICATIONS

Nokian Hakkapeliitta 1 Tire, 2000 Tread Design Guide, Jan. 2000, p. 53. 1/3.*
Toyo Proxes Z1 Tire, 2000 Tread Design Guide, Jan. 2000, p. 69. 3/5.*

* cited by examiner

Primary Examiner—Robert M. Spear
(74) *Attorney, Agent, or Firm*—David E. Wheeler

(57) **CLAIM**

The ornamental Design for a tire tread, as shown and described.

DESCRIPTION

FIG. **1** is a perspective view of a tire tread showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;
FIG. **2** is a front elevational view thereof;
FIG. **3** is a side elevational view thereof, the opposite side elevational view being a mirror image thereof;
FIG. **4** is an enlarged fragmentary perspective view;
FIG. **5** is a perspective view of a second embodiment of the tire tread;
FIG. **6** is a front elevational view of the tread in FIG. **5**;
FIG. **7** is a side elevational view of the tread in FIG. **5**, the opposite side elevational view being identical thereto; and,
FIG. **8** is an enlarged fragmentary perspective view of the tread in FIG. **5**.
In the drawings, the broken lines defining the sidewall and inner bead of the tire and the peripheral boundary between the tire tread and the sidewall are for illustrative purposes only and form no part of the claimed design.

1 Claim, 8 Drawing Sheets





FIG–1



FIG-2



FIG–3



FIG-4



FIG-5



FIG-6



FIG–7



FIG-8