



US00D458898S

(12) **United States Design Patent** (10) **Patent No.:** **US D458,898 S**
Shinmura (45) **Date of Patent:** **** Jun. 18, 2002**

(54) **TIRE TREAD**

(75) Inventor: **Yasushi Shinmura**, Kobe (JP)
(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)
(**) Term: **14 Years**

(21) Appl. No.: **29/151,917**
(22) Filed: **Dec. 11, 2001**

(30) **Foreign Application Priority Data**

Jun. 18, 2001 (JP) 2001-017642

(51) **LOC (7) Cl.** **12-15**
(52) **U.S. Cl.** **D12/596**
(58) **Field of Search** D12/560, 561,
D12/566, 567, 579, 596, 597, 600, 602,
603, 900; 152/209.1, 209.9, 209.12, 209.18,
209.25

(56) **References Cited**

U.S. PATENT DOCUMENTS

D309,592 S	*	7/1990	Shomura		D12/602
D326,071 S	*	5/1992	Enoki et al.		D12/596
D383,102 S	*	9/1997	Harris et al.		D12/600
D397,969 S	*	9/1998	Hino		D12/597
D421,944 S	*	3/2000	Welker		D12/602
D426,797 S	*	6/2000	Matsumura et al.		D12/602
D429,192 S	*	8/2000	Edwards et al.		D12/602

OTHER PUBLICATIONS

Dunlop SP779 Tire, 2000 Tread Design Guide, Jan. 2000, p. 88. 1/2.*
Kuhmo 932 Tire, 2000 Tread Design Guide, Jan. 2000, p. 137. 2/3.*
Ohtsu Hi-Steel Radial M-5100 Tire, 2000 Tread Design Guide, Jan. 2000, p. 147. 3/5.*

* cited by examiner

Primary Examiner—Robert M. Spear

(74) *Attorney, Agent, or Firm*—David L. King

(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire tread showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;


FIG. 2 is a front elevational view thereof;

FIG. 3 is a side elevational view thereof, the opposite side elevational view being identical thereto; and,

FIG. 4 is an enlarged fragmentary frontal view.

In the drawings, the broken lines defining the sidewall and inner bead and the peripheral boundary between the tire tread and the sidewall are for illustrative purposes only and form no part of the claimed design. The dark stippled surface shading represents the recessed portion of the tread grooves, having a depth as best shown along the left edge of FIG. 1.

1 Claim, 4 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4