

US00D460404S

(12) United States Design Patent (10) Patent No.:

Janjareh et al.

US D460,404 S

(45) Date of Patent: Jul. 16, 2002

WIDE TIRE TREAD (54)

Inventors: Ibrahim Mustafa Janjareh,

Greenville; Ralston Horace Moore, Fountain Inn, both of SC (US)

Michelin Recherche et Technique S.A. (73)Assignee:

(CH)

14 Years Term:

Appl. No.: 29/145,810

Jul. 30, 2001 (22)Filed:

(51)

U.S. Cl. D12/580 (52)

(58)D12/580, 588, 594, 595, 600, 601, 605, 900, 901; 152/209.1, 209.12, 209.16, 209.17,

209.25, 523, 524

References Cited (56)

U.S. PATENT DOCUMENTS

D334,362	S	3/1993	Stone et al	D12/147
D379,607	S *	6/1997	Lurois et al	D12/600
D380,995	S	7/1997	Grosskopf	D12/143
D387,310	S	12/1997	Scheuren et al	D12/143
D389,105	S *	1/1998	Lurois et al	D12/601
D394,029	S	5/1998	Gillard et al	D12/141
D399,461		10/1998	Lurois et al	D12/601
D422,896	S *	5/2001	Merino	D12/600

OTHER PUBLICATIONS

Mickey Thompson Competitor Tire, 2000 Tread Design Guide, Jan. 2000, p. 48. 4/5.*

Michelin XDA2 Tire, 2000 Tread Design Guide, Jan. 2000, p. 142. 3/4.*

Bridgestone VSW V-Steel Snow Wedge Tire, 2000 Tread Design Guide, Jan. 2000, p. 159. 3/4.*

Maragoni RD1 Ring Tread System Retread Tire, 2000 Tread Design Guide, Jan. 2000, p. 230. 1/3.*

Tread Design Guide, 1991, p. 146, Bridgestone V-steel rib 194.

Tread Design Guide, 1992, p. 63, Pirelli P7.

Tread Design Guide, 1998, p. 144, Heritage Super Fleet Cargo Carrier.

Tread Design Guide, 1998, p. 191, Firestone Flotation HF-1.

Tread Design Guide, 2000, p. 79, Aurora RF05.

Tread Design Guide, 2000, p. 113, Sumitomo Serengeti Touring A/S.

Tread Design Guide, 2000, p. 124, Cooper CSD 444.

Tread Design Guide, 2000, p. 144, Marshal Power Fleet 947.

* cited by examiner

Primary Examiner—Robert M. Spear (74) Attorney, Agent, or Firm—Martin Farrell; Robert R. Reed; Alan A. Csontos

CLAIM (57)

The ornamental design for a wide tire tread, as shown and described.


DESCRIPTION

FIG. 1 is a perspective view of a wide tire tread showing our new design, it being understood that the tread pattern is repeated over the outer circumference and shoulder of the tire, the opposite side perspective view being identical thereto; and,

FIG. 2 is an enlarged fragmentary front elevation view of the tread pattern of FIG. 1 showing our new tread pattern for the wide tire tread.

The broken line disclosure of the tire sidewall and inner bead is for illustrative purposes only and forms no part of the claimed design. In the drawings, the dark stippled shading in the groove area of the tread surface represents the recessed portion of the tread grooves, having recesses best illustrated by the top and bottom boundaries of FIG. 2.

1 Claim, 2 Drawing Sheets






Fig. 1




Fig. 2

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : Des. 460,404 S

DATED : July 16, 2002 INVENTOR(S) : Janajreh et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [75], first-named inventor is written as follows:

-- Ibrahim Mustafa Janajreh --

Signed and Sealed this

Fourth Day of February, 2003

JAMES E. ROGAN

Director of the United States Patent and Trademark Office